

ROCKHARD Quick Seal

A fast-drying water repellent clear primer/sealer designed to enhance surface appearance and protect stone, concrete & masonry surfaces from water damage by creating a long lasting impervious Silicon Dioxide (SiO₂) barrier that provides superior resistance to water, mold, airborne dust and dirt, alkali, freeze/thaw damage and spills. Mix a concrete stain directly into Quick Seal & Enhance to stain and seal in one step.

CHARACTERISTICS

- Solvent Based
- VOC <20g/ liter
- Clear color enhancing; can be tinted

SURFACES

- Unglazed tile
- Natural and artificial stone
- Concrete/pavers/brick/cement block
- Cannot be applied to painted surfaces

BENEFITS

- Creates a film for ROCKHARD T200 to adhere to and prevent unnecessary absorption of topcoat.
- Prevents damage from moisture, staining, dirt and soil build ups, mold & mildew growth
- ROCKHARD QUICK SEAL is UV stable and non-slip

APPLICATION METHOD

- Using an Acetone Safe pump sprayer fitted with a red fan tip or an adjustable conical tip. Keep tip elevated off floor between 12-18". Spray the product with a 50 % overlap of previous sweep of the wand. When using a conical tip, move the wand in a circular fashion as you advance the spray with a 50% overlap of the previous sprayed area.

CARE & MAINTENANCE

- Surface should be swept and mopped or hosed as needed
- If wear develops from heavy traffic, lightly sand affected area with 220 grit sanding pad and re-apply product

SURFACE PREPARATION

- Surface must be clean, dry and in sound condition. All silicone sealers removed.
- If using a stain pigment, mix 1 hour before application.
- New concrete must be fully cured for 7 days from date of pour. Moisture content <13%.
- Abrade all hard troweled concrete to 220 grit finish. Use a 50% acetone to 50% water solution to remove accumulated slurry.

SAFETY MEASURES

- Be sure to incorporate PPP when applying ROCKHARD QUICK SEAL
- When indoors, it is highly recommended to wear an adequate vapor fitted respirator.
- Be careful to prevent contact with skin.

PRODUCT COST

- 1 gal. \$75.00 Gloss / Satin



COVERAGE RATE:

150-500 sq.ft./Gal.
(depending on surface and porosity)