### **XPS-ECTM Flexible Membrane - A**

<b>SECTION 1. IDENTIFICA</b>	TION
Product identifier	XPS-ECTM Flexible Membrane
Other Means of Identification	None
Recommended Use	Epoxy Resin
Restrictions on Use	Unknown
Supplier Identifier	Xtreme Polishing Systems 2200 NW 32 St. #700 Pompano Beach, FL 33069 USA Web: <u>www.ShopXPS.com</u>
Emergency Phone No.	24-Hour Emergency Telephone (CHEMTEL) : (800) 255-3924 Contract # MIS7038570

#### **SECTION 2. HAZARD IDENTIFICATION**

Classification	Skin Sensitization Category 1B
	Skin Corrosion/irritation Category 2
	Serious eye damage/irritation Category 2A
	Acute Toxicity, Oral Category 5
	Hazardous to the aquatic environment - acute Category 2
	Hazardous to the aquatic environment - chronic Category 2

Product Identifier: XPS-ECTM Flexible Membrane A

Date of Preparation: August 2020

ATTERS OF A



Page 1 of 8

# Safety Data Sheet

#### Label Elements



P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash with plenty of water and soap thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/eye protection. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. P337 + P313 If eye irritation persists: Get medical advice/attention. P302 + P352 IF ON SKIN: Wash with plenty of water. P333 + P313 If skin irritation or rash occurs: Get medical advice/attention. P312 IF SWALLOWED: Call a

Product Identifier: XPS-ECTM Flexible Membrane A

Page 2 of 8

Date of Preparation: August 2020





POISON Center/doctor/...if you feel unwell. P362 + P364 Take off contaminated clothing and wash before reuse. P273 Avoid release to the environment. P391 Collect spillage. P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

#### Other Hazards: Unknown

Chemical Name	CAS No.	% concentration
Reaction product: bisphenol-A-	25085-99-8	50 - 90%
(epichlorhydrin) epoxy resin		
alkyl glycidyl ether	68609-97-2	1 - 8 %
benzyl alcohol	100-51-6	1 - 8 %
Phenol, 4-Nonyl-,- branch	84852-15-3	15-85

#### **SECTION 4. FIRST-AID MEASURES**

#### First-aid Measures

#### Ingestion:

IF SWALLOWED: Call a POISON Center/doctor/...if you feel unwell.

#### Skin Contact:

Flush with soap and water for a minimum of 15 minutes. Consult a physician if irritation persists or you feel unwell.

#### Eye Contact:

Rinse immediately with plenty of water for at least 15 minutes. Consult a physician.

#### Most Important Symptoms and Effects, Acute and Delayed

#### If inhaled:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### If on skin:

Harmful if in contact with the skin. Causes skin irritation. Exposure may produce an allergic reaction

If in eyes:

Causes serious eye damage.

#### If Ingested:

Ingestion is likely to be harmful or have adverse effects

#### Immediate Medical Attention and Special Treatment:

#### **Special Instructions:**

If a physician or medical attention is required, have product container or label at hand.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

#### **Extinguishing Media**

#### Suitable Extinguishing Media

In case of fire: water fog, foam, dry chemical powder, carbon dioxide (CO2) **Unsuitable Extinguishing Media** 

water jet

#### Specific Hazards Arising from the Product

During fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating.

#### Special Protective Equipment and Precautions for Fire-fighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and protective firefighting clothing. Avoid contact with this material during fire-fighting operations. If contact is likely, change to full chemical resistant fire-fighting clothing with self-contained breathing apparatus.

Product Identifier: XPS-ECTM Flebible Membrane

Page 2 of 8

Date of Preparation: August 2020





#### SECTION 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions, Protective Equipment, and Emergency Procedures** Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.

#### Methods and Materials for Containment and Clean up

For containment, ensure adequate ventilation and absorb any spill with inert liquid binding material and dispose of waste safely.

#### SECTION 7. HANDLING AND STORAGE

#### **Precautions for Safe Handling**

Avoid prolonged or repeated contact with skin. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid use of electric band heaters. Avoid release to the environment. Observe good industrial hygiene practices.

#### Conditions for Safe Storage

Store in cool dry and well-ventilated place. Keep stored in accordance with local, regional, national, and international regulations. Store away from incapable materials.

#### **SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

#### **Control Parameters**

All protective clothing should be appropriately clean and available to dress into before work. The engineering measures or controls and PPE recommendations are only guidelines and may not apply to every situation.

Data not available. For additional information, please consult the corresponding requirements under <u>http://www.ccohs.ca/topics/hazards/chemical/chemicals/</u>

	ACGIH <sup>®</sup> TLV <sup>®</sup>		OSHA PEL		AIHA <sup>®</sup> WEEL <sup>®</sup>	
Chemical Name	TWA	STEL [C]	TWA	Ceiling	8-hr TWA	Short-term

#### Appropriate Engineering Controls

Local exhaust ventilation required. Make up air should be supplied to balance air that is removed by local or general exhaust ventilation. Provide sufficient ventilation to keep vapors below permissible exposure limit. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national / local regulations are observed.

#### Individual Protection Measures

Product Identifier: XPS-ECTM Flexible Membrane A

Page 3 of 8

Date of Preparation: August 2020



## **Safety Data Sheet**





#### **General Measures**

Do not eat, drink or smoke during work. Avoid all contact with skin or eye. If clothing comes into contact with material, do not allow out of the workplace. Clean hands and any exposed skin thoroughly after work and before breaks.

#### Eye / Face Protection

Use tightly sealed goggles or safety glasses with side shields which are resistant to Chemicals.

#### **Skin Protection**

Wear chemical resistant protection gloves. Wear impervious clothing as necessary to protect against coming in contact with product.

#### **Respiratory Protection**

If insufficient ventilation, wear respiratory protection.

SECTION 9. PHYSICAL AND CHEMICAL PR	OPERTIES
Appearance	Clear Liquid
Odor	Not available
Odor threshold	Not available
рН	Not available
Melting Point	Not available
Initial Boiling Point / Range	Not Available
Flash point	>93
Evaporation rate	Not available
Flammability(solid; gas)	Not available
Lower flammable/explosive limit	Not available
Upper flammable/explosive limit	Not available
Vapor pressure	Not available
Vapor density	Not available
Specific gravity	Not available
Solubility	Partial
Partition coefficient – n- Octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available

SECTION 10. STABILITY AND REACTIVITY	
Reactivity	Non-reactive
Chemical stability	Stable under recommended handling and storage conditions
Possibility of Hazardous reactions	This product will polymerize if mixed with an amine. Considerable heat can evolve.
Conditions to avoid	Avoid temperatures exceeding the

Product Identifier: XPS-ECTM Flexible Membrane A

Date of Preparation: August 2020

Page 4 of 8



	flash point. Avoid unintended contact with amines.
Incompatible materials	Strong oxidizers, strong alkalis, strong mineral acids, amines.
Hazardous decomposition products	Unknown

### SECTION 11. TOXICOLOGY INFORMATION

	LOGY INFO	RIVIATION		
Likely Routes of Admi	nistration			
Inhalation, skin contact,	eye contact	, ingestion.		
Acute Toxicity				
Oral: Harmful if swallowed.				
Dermal: Harmful in contact with skin.				
LD50 and LC50 Data				
Not available				
Skin Corrosion/Irritatio	on			
Causes skin irritation.				
Serious Eye Damage/	rritation			
Causes serious eye dan	nage			
STOT (Specific Target	Organ Toxi	icity) – Single I	Exposure Inha	lation
No data	-			
Aspiration Hazard				
Not classified based on	available da	ita.		
STOT(Specific Target	Organ Toxid	city) – Repeate	d Exposure	
No data				
Respiratory and/or Ski				
May irritate mucous me				
asthma attack to person				
concentrations may lead				
are usually reversible. M				ns of nausea, light-
headedness, drowsines	s, dizziness,	, loss of coordin	ation	
Carcinogenicity				
Unknown				
Chemical Name IA	RC	ACGIH®	NTP	OSHA
Reproductive Toxicity				
Not available				
Not available Germ Cell Mutagenicit	y			
Not available Germ Cell Mutagenicity Not available	y			
Not available Germ Cell Mutagenicit	y			

#### SECTION 12. ECOLOGICAL INFORMATION

Hazardous to aquatic environment This is not required by WHMIS

Product Identifier: XPS-ECTM Flexible Membrane A

Date of Preparation: August 2020



Page 5 of 8



### **Safety Data Sheet**



#### This is not required by OSHA HCS 2012

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

#### Disposal Methods

Dispose of contents/container into safe container in accordance with local, regional or national regulations.

#### **SECTION 14. TRANSPORT INFORMATION**

<u>UN Number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations:</u> UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol-A-(epichlorhydrin) epoxy resin); CLASS 9; PG III

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime): UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol-A-(epichlorhydrin) epoxy resin); CLASS 9; PG III; MARINE POLLUTANT

<u>UN Number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air):</u> UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol-A-(epichlorhydrin) epoxy resin); CLASS 9; PG III; MARINE POLLUTANT

#### **SECTION 15. REGULATORY INFORMATION**

Not required under Canadian Regulations.

#### **SECTION 16. OTHER INFORMATION**

SECTION 10. OTHER IN	
Date of Preparation	August 2020
Date of Last Revision	June 1, 2014
Revision Indicators	The entire MDSD was change in August 2020 to be in accordance with the WHMIS 2015 which incorporates the Globally Harmonized System of Classification and Labeling of Chemicals for Canadian Workplaces.
References	<ol> <li>CHOHS Fact Sheets September 2016 ©CCOHS 2016</li> <li>Supplier's Material Safety Data Sheet(s)</li> </ol>
ACGIH ATE CAS DSL IARC IATA IMDG LC LD NIOSH NTP OSHA PEL STEL TDG TLV TSCA TWA	American Conference of Governmental Industrial Hygienists         Acute toxicity estimate         Chemical Abstract Service         Domestic Substance List         International Agency for Research on Cancer         International Air Transport Association         International Maritime Dangerous Goods Code         Lethal concentration         Lethal Dosage         National Institute for Occupational Safety and Health         National Toxicology Program (U.S.A.)         Occupational Safety and Health Administration (U.S.A.)         Permissible Exposure Limit         Short-term Exposure Limit         Transport of dangerous goods in Canada         Threshold Limit Value         Toxic Substances Control Act         Time Weighted Average
WHMIS	Workplace Hazardous Materials Information System

Product Identifier: XPS-ECTM Flexible Membrane A

Date of Preparation: August 2020

Page 6 of 8

www.shopxps.com

<u>Notice:</u> The facts stated and the recommendations made with respect to the use of this product are based on liable information. No guarantee of accuracy is made. Before using, determine the suitability of the product's intended use. The purchaser assumes all risks and liability for losses, damage, or expenses, directly or indirectly, arising from the handling or use of the product or from any other cause. All recommendations are made on condition that Xtreme Polishing Systems will not be liable for any damages resulting from its use since Xtreme Polishing Systems cannot control the conditions under which the product will be transported, stored, handled or used by the purchaser.

Product Identifier: XPS-ECTM Flexible Membrane A

Date of Preparation: August 2020

