

Page 1/11

Safety Data Sheet acc. to OSHA HCS


Printing date 03/15/2024

Reviewed on 03/15/2024

1 Identification

- · Product identifier
- · Trade name: XPS-72 Flex Part A
- · Article number: 211-XTRM-A
- · Details of the supplier of the safety data sheet
- *Manufacturer/Supplier: Xtreme Polishing Systems* 2200 NW 32nd St., Suite 700 Pompano Beach, FL 33069
- Information department: Product safety department
 Emergency telephone number: During normal opening times: +1 (800) 659-5843

2 Hazard(s) identification



∠) US Page 2/11

Printing date 03/15/2024

Trade name: XPS-72 Flex Part A

Safety Data Sheet acc. to OSHA HCS

Reviewed on 03/15/2024

(Contd. of pa	age 1)
· Signal word Danger	
Hazard-determining components of labeling: tatractive N.N. (mathylanadiavalabeyana, 4.1 div/bia, DL, canadata	
tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate	
Solvent naphtha (petroleum), light arom.	
bis(4-(1,2-bis(ethoxycarbonyl)ethy-lamino)-3-methylcyclohexyl)methane Stoddard solvent	
(R)-p-mentha-1,8-diene	
Hazard statements	
Flammable liquid and vapor.	
Causes skin irritation.	
Causes serious eye irritation.	
May cause an allergic skin reaction.	
May cause genetic defects.	
May cause cancer.	
· Precautionary statements	
If medical advice is needed, have product container or label at hand.	
Keep out of reach of children.	
Read label before use.	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Keep container tightly closed.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling.	
Contaminated work clothing must not be allowed out of the workplace.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and	easv
to do. Continue rinsing.	,
IF exposed or concerned: Get medical advice/attention.	
Specific treatment (see on this label).	
Take off contaminated clothing and wash it before reuse.	
If skin irritation or rash occurs: Get medical advice/attention.	
If eye irritation persists: Get medical advice/attention.	
Wash contaminated clothing before reuse.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulations.	
· Classification system:	
NFPA ratings (scale 0 - 4)	
Health = 0	
Fire = 2	
0 Reactivity = 0	
· HMIS-ratings (scale 0 - 4)	
HEALTH *2 Health = *2	
$\frac{FRE}{2} Fire = 2$	
REACTIVITY 0 Reactivity = 0	
(Contd. on pa	age 3)

-US-

Trade name: XPS-72 Flex Part A

Safety Data Sheet

(Contd. of page 2)

- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

>25-≤50%
>25-≤50%
>2.5-≤10%
>2.5-≤10%
>2.5-≤10%
≥0.1-<1%
≥0.1-≤2.5%

4 First-aid measures

- · Description of first aid measures
- · After inhalation:
- Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

• Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

US

Page 4/11

Printing date 03/15/2024

Trade name: XPS-72 Flex Part A

Reviewed on 03/15/2024

	(Contd. of page 3)
 Environmental precautions: 	
Do not allow product to reach sewage system or any water course.	
Inform respective authorities in case of seepage into water course or sewage system.	
Do not allow to enter sewers/ surface or ground water.	
Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, saw	/dust).
Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.	
Do not flush with water or aqueous cleansing agents	
· Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
Protective Action Criteria for Chemicals	
· PAC-1:	
5989-27-5 (<i>R</i>)-p-mentha-1,8-diene	15 ppm
60-00-4 edetic acid	4.1 mg/m ³
8052-41-3 Stoddard solvent	300 mg/m ³
628-63-7 pentyl acetate	100 ppm
PAC-2:	
5989-27-5 (R)-p-mentha-1,8-diene	67 ppm
60-00-4 edetic acid	45 mg/m³
8052-41-3 Stoddard solvent	1,800 mg/m ³
628-63-7 pentyl acetate	670 ppm
PAC-3:	
5989-27-5 (<i>R</i>)-p-mentha-1,8-diene	170 ppm
60-00-4 edetic acid	200 mg/m³
8052-41-3 Stoddard solvent	29500** mg/m³
628-63-7 pentyl acetate	4000* ppm

7 Handling and storage

- · Handling:
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- [.] Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

(Contd. on page 5)

Reviewed on 03/15/2024

Trade name: XPS-72 Flex Part A

(Contd. of page 4)

	itional information about design of technical systems: No further data; see item 7.
• Com The reco	t rol parameters ponents with limit values that require monitoring at the workplace: following constituent is the only constituent of the product which has a PEL, TLV or oth mmended exposure limit. is time, the other constituents have no known exposure limits.
8052	-41-3 Stoddard solvent
PEL	Long-term value: 2900 mg/m³, 500 ppm
	Long-term value: 350 mg/m³ Ceiling limit value: 1800* mg/m³ *15-min
TLV	Long-term value: 525 mg/m³, 100 ppm
	tional information: The lists that were valid during the creation were used as basis.
Avoid Brea In ca expo	e protective clothing separately. d contact with the eyes and skin. thing equipment: use of brief exposure or low pollution use respiratory filter device. In case of intensive or long sure use respiratory protective device that is independent of circulating air. e ction of hands:
	Protective gloves
Due prep Sele	glove material has to be impermeable and resistant to the product/ the substance/ the preparation to missing tests no recommendation to the glove material can be given for the product/ t
	aration/ the chemical mixture. ction of the glove material on consideration of the penetration times, rates of diffusion and a adation
• Mate The qual subs be cl	aration/ the chemical mixture. ction of the glove material on consideration of the penetration times, rates of diffusion and adation rial of gloves selection of the suitable gloves does not only depend on the material, but also on further marks ity and varies from manufacturer to manufacturer. As the product is a preparation of seve
• Mate The qual subs be cl • Pene	aration/ the chemical mixture. ction of the glove material on consideration of the penetration times, rates of diffusion and adation vrial of gloves selection of the suitable gloves does not only depend on the material, but also on further marks ity and varies from manufacturer to manufacturer. As the product is a preparation of seve tances, the resistance of the glove material can not be calculated in advance and has therefore necked prior to the application.

(Contd. on page 6)

Trade name: XPS-72 Flex Part A

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

Information on basic physical and cl General Information	
Appearance:	
Form:	Liquid
Color:	Clear
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	139 °C (282.2 °F)
· Flash point:	23 - 60 °C (73.4-140 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	450 °C (842 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
[.] Danger of explosion:	Product is not explosive. However, formation of explosive air. vapor mixtures are possible.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 50 °C (122 °F):	38.6 hPa (29 mm Hg)
· Density at 20 °C (68 °F):	1.12 g/cm³ (9.35 lbs/gal)
[.] Relative density	Not determined.
[.] Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Miscible
· Partition coefficient (n-octanol/water): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	8.9 %
VOC content:	8.88 %
	99.5 g/l / 0.83 lb/gal
Solids content:	59.0 % (by weight)
	(Contd. on page 7

Safety Data Sheet acc. to OSHA HCS

Reviewed on 03/15/2024

(Contd. of page 5)

Page 7/11

Safety Data Sheet acc. to OSHA HCS

Printing date 03/15/2024

Trade name: XPS-72 Flex Part A

Reviewed on 03/15/2024

(Contd. of page 6)

• Other infomation:

No further relevant information available.

10 Stability and reactivity

- Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

5989-27-5 (R)-p-mentha-1,8-diene

Oral LD50 4,400 mg/kg (rat)

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

- Irritant
- Carcinogenic.

The product can cause inheritable damage.

· Carcinogenic categories

IARC (International Agency for Research on Cancer)

5989-27-5 (*R*)-*p*-*m*entha-1,8-diene

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.

(Contd. on page 8)

3

US

Trade name: XPS-72 Flex Part A

Safety Data Sheet acc. to OSHA HCS

Reviewed on 03/15/2024

(Contd. of page 7)

- Behavior in environmental systems:
 Bioaccumulative potential No further relevant information available.
- **Mobility in soil** No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground. Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, IMDG, IATA	UN1263	
UN proper shipping name		
DOT	Paint	
IMDG, IATA	PAINT	
Transport hazard class(es)		
DOT		
Class	3 Flammable liquids	
Label	3	
IMDG, IATA		
Class	3 Flammable liquids	
Label	3	

Trade name: XPS-72 Flex Part A

Reviewed on 03/15/2024

	(Contd. of p
Packing group DOT, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	30
EMS Number:	F-E,S-E
Stowage Category	A
Transport in bulk according to Annex	all of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III
<u> </u>	

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

• Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· TSCA new (21st Century Act) (Substances not listed)

623-91-6 diethyl fumarate

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

(Contd. on page 10)

US

Trade name: XPS-72 Flex Part A

Safety Data Sheet acc. to OSHA HCS

Reviewed on 03/15/2024

(Contd. of page 9)

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling: tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate Solvent naphtha (petroleum), light arom. bis(4-(1,2-bis(ethoxycarbonyl)ethy-lamino)-3-methylcyclohexyl)methane Stoddard solvent (R)-p-mentha-1,8-diene · Hazard statements Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause genetic defects. May cause cancer. · Precautionary statements If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsina. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep cool. (Contd. on page 11)

– ús

Page 11/11

Printing date 03/15/2024

Trade name: XPS-72 Flex Part A

Safety Data Sheet acc. to OSHA HCS

Reviewed on 03/15/2024

(Contd. of page 10)

US

Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

- Information about limitation of use: Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this
- preparation. Exceptions can be made by the authorities in certain cases.
- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

- · Date of preparation / last revision 03/15/2024 / -
- Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Liq. 3: Flammable liquids - Category 3 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Skin Sens. 1: Skin sensitisation - Category 1 Muta. 1B: Germ cell mutagenicity - Category 1B Carc. 1B: Carcinogenicity - Category 1B

[·] Contact: Mr. Williams