

SAFETY DATA SHEET

1 PRODUCT AND COMPANY IDENTIFICATION

Supplier Details: Xtreme Polishing Systems
2200 NW 32nd St., Ste. 700
Pompano Beach, FL 33069-1098

Product: Xtreme Fill 85 B

Phone: (877) 908-3952

Web: www.xtremepolishingsystems.com

Emergency: (323) 908-3952 (24 HOURS)

2 HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Environmental, Hazards to the aquatic environment - Acute, 1
Environmental, Hazards to the aquatic environment - Chronic, 1
Health, Specific target organ toxicity - Repeated exposure, 2
Health, Serious Eye Damage/Eye Irritation, 2 A
Health, Acute toxicity, 4 Oral

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **WARNING**

GHS Hazard Pictograms:



GHS Hazard Statements:

H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
H373 - May cause damage to organs (state all organs affected, if known) through prolonged or repeated exposure.
H319 - Causes serious eye irritation
H302 - Harmful if swallowed

GHS Precautionary Statements:

P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P264 - Wash hands thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301 + P312 - IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 - Get medical advice/attention if you feel unwell.
P330 - Rinse mouth.
P337 + P313 - If eye irritation persists: Get medical advice/attention.
P391 - Collect spillage.
P501 - Dispose of contents/container according to state, local and federal regulations.

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: Eyes; Ingestion; Inhalation; Skin;

Target Organs: Eyes; Skin; Respiratory system;

Inhalation: Heating, spraying, foaming or otherwise mechanically dispersing operations way generate vapor

or aerosol concentrations sufficient to cause irritation or other adverse effects. Minimal respiratory tract irritation may occur with exposure to a large amount of material.

Skin Contact: Prolonged or repeated exposure can cause skin irritation or dermatitis in some individuals.
Eye Contact: May cause watering of the eye and irritation of the conjunctiva.
Ingestion: May cause nausea or vomiting.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Ingredients:		
CAS#	%	Chemical Name:
102-60-3	5-25%	2-Propanol, 1,1',1'',1'''-(1,2-ethanediyl)dinitrilo)tetrakis-
5285-60-9	0-5%	Benzenamine, 4,4'-methylenebis[N-(1-methylpropyl)-
68479-98-1	0-4%	Benzenediamine, ar,ar-diethyl-ar-methyl-

4 FIRST AID MEASURES

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility immediately.

Skin Contact: Remove all contaminated clothing and shoes. Wash skin with large quantities of water and soap. Wash clothing before wearing again and clean shoes. If redness, itching or a burning sensation develops or persists after the area is washed, consult a physician.

Eye Contact: Flush with large amounts of water for 15 minutes. Use fingers to assure that the eyelids are separated and that the eye is being irrigated. Get immediate medical attention.

Ingestion: If swallowed, do not induce vomiting unless directed to do so by medical personnel. This material is an aspiration hazard. Never give anything by mouth to an unconscious person. Seek medical attention.

5 FIRE FIGHTING MEASURES

Flash Point: >200°F
Flash Point Method: COC
Dry powder, foam, carbon dioxide. Use cold water spray to cool fire exposed containers to minimize risk of rupture. A solid stream of water directed into hot burning liquid could cause frothing. If possible, contain fire run off.

6 ACCIDENTAL RELEASE MEASURES

Spill: Remove all sources of flames, heating elements, gas engines, etc. Emergency clean-up personnel should wear chemical goggles, rubber or plastic gloves and clothing as required to protect against contact. Prevent spreading and contamination of surface waters and drinking supplies. Notify local health officials and other appropriate agencies if such contamination should occur.

Clean up: With adequate ventilation and appropriate personal protective equipment, cover the area with an inert absorbent material such as clay or vermiculite and transfer to steel waste containers. Ventilate area to remove the remaining vapors.

7 HANDLING AND STORAGE

Handling Precautions: Do not smoke or use naked lights, open flames, space heaters or other ignition sources near pouring, frothing or spraying operations. If contamination with isocyanates is suspected, do not reseal containers. Special Emphasis for spray applications of mixed products containing isocyanates: Inspect the application area for potential to expose other persons or for overspray to drift onto buildings, vehicles or other property. When spraying building exteriors, persons entering or exiting the building as well as those inside could be exposed to polyisocyanates due to wind conditions, open windows or air intakes. Do not begin application work until these potential problems have been corrected.

Storage Requirements: When stored between 60°-85° F in sealed containers, typical shelf life is 6 months or more from the date of manufacture. Open containers must be handled properly to prevent moisture pickup.

Engineering Controls:	All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Uses requiring heating and/or spraying may require more aggressive engineering controls or PPE.
Personal Protective Equipment:	2-Propanol, 1,1',1'',1'''-(1,2-ethanediyldinitrilo)tetrakis- cas#:(102-60-3) [5-25%] Personal protective equipment Respiratory protection: Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Hand protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Splash contact Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 120 min Material tested:Camatril (KCL 730 / Aldrich Z677442, Size M) data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374 If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario. Eye protection: Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Skin and body protection: Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

2-Propanol, 1,1',1'',1'''-(1,2-ethanediyldinitrilo)tetrakis- cas#:(102-60-3) [5-25%]

Appearance:	Non-Pigmented liquid.	Viscosity:	Approx. 800 cps
Physical State:	Liquid	Odor:	Mild
Spec Grav./Density:	8.52 lbs/gallon	Flash Point:	>200°F
Boiling Point:	>354°F	Vapor Density:	>1
Flammability:	None Flammable		
Evap. Rate:	<1		

Reactivity:	No specific data
Chemical Stability:	Product is stable under normal conditions.
Conditions to Avoid:	No specific data
Materials to Avoid:	No specific data
Hazardous Decomposition:	Under normal storage conditions hazardous decomposition products should not be produced.
Hazardous Polymerization:	Will not occur.

2-Propanol, 1,1',1'',1'''-(1,2-ethanediyldinitrilo)tetrakis- cas#:(102-60-3) [5-25%]

Information on toxicological effects

Acute toxicity:

Oral LD50 no data available

Inhalation LC50

Dermal LD50

Other information on acute toxicity

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: no data available

Respiratory or skin sensitisation: May cause allergic skin reaction.

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System):
no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System):
no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Synergistic effects: no data available

Additional Information:

RTECS: UB5604000

2-Propanol, 1,1',1'',1'''-(1,2-ethanediyldinitrilo)tetrakis- cas#:(102-60-3) [5-25%]

Information on ecological effects

Toxicity: no data available

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: no data available

13	DISPOSAL CONSIDERATIONS
----	--------------------------------

Disposal: Any disposal practice must be in compliance with all federal, state and local laws and regulations. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate or otherwise inappropriate. Waste characterization and disposal compliance are the responsibility solely of the party generating the waste or deciding to discard or dispose of the material.

Do not allow material to enter sewers, a body of water, or contact the ground. Refer to RCRA 40 CFR 261, and/or any other appropriate federal, state or local requirements for proper classification information.

14	TRANSPORT INFORMATION
----	------------------------------

DOT - Non DOT/non-RCRA regulated

IATA/IMDG/ICAO - Not dangerous goods

15	REGULATORY INFORMATION
----	-------------------------------

[%] RQ (CAS#) Substance - Reg Codes

[5-25%] 2-Propanol, 1,1',1",1"'-(1,2-ethanediyldinitrilo)tetrakis- (102-60-3) TSCA

[0-5%] Benzenamine, 4,4'-methylenebis[N-(1-methylpropyl)- (5285-60-9) TSCA

[0-4%] Benzenediamine, ar,ar-diethyl-ar-methyl- (68479-98-1) TSCA

This product does not contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

Regulatory Code Legend

TSCA = Toxic Substances Control Act

16	OTHER INFORMATION
----	--------------------------

NFPA: Health = 1, Fire = 1, Reactivity = 0, Specific Hazard = None

HMIS III: Health = 1, Fire = 1, Physical Hazard = 0

HMIS PPE: X - Consult your supervisor for special instructions



Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

Revision Date: 6/21/2019