



THIXO 5

Synthetic Thickener

L hfYa Y`Dc`Jg\Jb[`GmgHYa g

PRODUCT DESCRIPTION	<p>Thixo-5 is a fluffed and dried synthetic polyethylene pulp. It is non-hazardous, resists mildew and biological growth and can be used in a wide variety of applications including adhesives, textured, cement, or industrial coatings and sealants. It is used in various applications to improve their dimensional stability, strength, and crack resistances.</p>	
TECHNICAL PROPERTIES	Base	Polyethylene polymer powder
	Color	White fluffy fibers
	Odor	No significant odor
	Melting point (°C)	125-135 °C
	Specific Gravity	0.96 g/cm ³
	Shelf Life	2 years in unopened containers.
	VOC (g/L)	0 g/L
CAUTION	<p>Fiber dust should be considered a nuisance. Avoid breathing dust and control dust accumulations. Avoid the use of air jets if possible to prevent fibers from becoming airborne. Wash hands and skin thoroughly after handling. Consult the material safety data sheet for further information.</p>	
IMPORTANT NOTICE	<p>All statements, recommendations and technical information contained in this document are based on tests and information, which Xtreme Polishing Systems believes to be accurate as of this date; the buyer however should test this product before use. Xtreme Polishing Systems assumes no obligation or liability for results obtained from the use of this product. The product and information herein are furnished at the buyer's risk. Xtreme Polishing Systems will not be liable for any direct, indirect, consequential, economic or any other damage whatsoever except to replace the product and or refund the purchase price to the purchaser.</p>	

XTREME POLISHING SYSTEMS

2200 NW 32nd Street #700, Pompano Beach, FL 33069

Tel: 800.255.3924 www.shopxps.com