

LS38BLACK Service temperature wine cellar Service range





PRESERVIN: Simply connect the cap to the pump hose press the empty air button. The operation takes about 1 minute.



Our products are manufactured in compliance with European environmental rules. Especially, refrigerant fluid (R600a) doesn't reject neither CFC nor HFC and respect environment.

Energy consumption is calculated based on the result obtained for 24h in standard test conditions. The actual energy consumption depends on the conditions of use and location of the device.

This equipment is designed to be used in an ambient temperature between 16-32°

This appliance is intended to be used exclusively for the storage of wine.

Alcohol abuse is dangerous for health, please consume in moderation.

*Capacity given as an indication with 75cl Bordeaux traditional type bottles and measured with 4 shelves. Adding shelves reduce considerably the total

capacity.

**Thanks to the Vinotag® application, benefit from a digital register of your wine cellar and be alerted of the peak dates of your wines. In partnership with Vivino, scan your bottle to access its pre-filled wine sheet.

- Capacity: 38 bottles*
- ♣ Vinotag compatible**
- Free standing installation
- Design: black
- Cooling system: compressor
- Type of cold: air moving system
- Adjustable temperature range of use: 5 -20
 °C
- Electronic regulation
- Thermometer with white digital display
- ♣ White LED lights with switch button
- Humidity control: natural (hygrodynamy concept)
- 1 glass door, 2-layers tempered glass

TO THE NEAREST DEGREE

Bring your wines to tasting temperature to take full advantage of all their aromas. Its digital control panel allows intuitive use.

PRESERVIN: BUILT-IN AIR VACUUM

Keep your wines for up to 3 weeks after opening thanks to the Préservin system. The vacuum pump integrated in the tank of your cellar allows you to store up to 3 open bottles of wine, in a vertical position, for several days.

A true innovation, PRESERVIN reduces the volume of air (oxygen) present in the bottle after opening, thus delaying the oxidation of the wine and preserving the freshness and the organoleptic and olfactory qualities of the wine for longer.

OPTIMIZED STORAGE

Store your wines on its steel wire shelves, natural wood front, up to 38 Bordeaux-type 75 cl bottles. Identify your wines in a few minutes thanks to the pediments of the shelves which can accommodate labels to identify your bottles.



LS38BLACK Service temperature wine cellar Service range





> EQUIPMENTS INCLUDED

- 2 semi-sliding wire shelves , wooden front
- 2 semi-sliding wire half-shelves, wooden front
- 4 adjustable feet
- Anti-vibration system

> TECHNICAL CHARACTERISTICS

■ Energy class: G

■ Annual electrical consumption: 125 kWh

Climatic class: SN-STNoise level: 39 dB

■ EEI: 153.50

Voltage: 220-240 V
Power input: 50 W
Category: 2 - Wine cellar
Type of gas: R600a

> SAFETY

Visual and audible alarms: notify you when your attention is required

> VINOTAG® APPLICATION

Free wine cellar management application. Access a virtual representation of your wine cellar and a detailed inventory of its contents.

> COMPATIBLE ACCESSORIES

Only available in spare parts

> LOGISTIC DATAS

Gross dimensions (WxDxH cm) : $43.5 \times 59 \times 87$ Net dimensions (WxDxH cm) : $40 \times 56.5 \times 85.5$

Gross weight (kg) : 31.00

Net weight (kg) : 29.00

Full truck (pcs) : 220

Container (pcs) 20' : 116

40' : 239 40' HC : 300

Gencod 3541362209238

Non-contractual pictures Last update: 03/08/2023