


E27 PENDANT LAMP - EU VERSION

MATTIAS STÅHLBOM ON THE DESIGN "The simplicity of the naked bulb is hard to compete with. It stands for something that feels romantic and contemporary at the same time. E27 departs from the essence of a lamp - the socket - creating a simple yet strong object that celebrates the potential beauty in simplicity."



12,5 cm 5"

CEILING CAP



5,6 cm / 2.2"

Ø 9 cm / 3.5"

CEILING CAP FOR MULTIPLE LAMPS



Ø 19.7 cm / 5"

READY-TO-SHIP OPTIONS





DESIGNED BY / YEAR OF DESIGN

Mattias Ståhlbom / 2008

ABOUT THE DESIGNER

Mattias Ståhlbom is an internationally successful architect and partner at the Stockholm-based architecture and design studio TAF. TAF's aim is to make ordinary life less ordinary through subtle but effective changes in how products and architecture appear and function. Mattias Ståhlbom's products have been exhibited at prestigious venues such as MOMA and the Swedish National Museum in Stockholm.

CATEGORY

Pendant lamp

ENVIRONMENT

Indoor

DESCRIPTION

The E27 Pendant Lamp can be used as a single light source, in pairs, rows or even in clusters to create a modern Scandinavian chandelier. To create clusters the E27 Multiple Ceiling cap can be used to gather up to 14 E27 Pendant Lamps.

PRODUCTION PROCESS

The E27 Pendant Lamp is pressed in vulcanised silicone rubber under high temperature. The cord is extruded. Inside socket and cord is assembled by hand.

MATERIAL

Silicone rubber, plastic socket and PVC cord.

CORD LENGTH

400 cm / I57.5"

Extra cord can be purchased seperately.

BULB INCLUDED

Yes

CEILING CAP INCLUDED

Yes - White. Multiple ceiling cap can be purchased seperately.

DIMMABLE FUNCTION

CLEANING AND CARE

Clean with soft dry cloth only. Always switch off the electricity supply before cleaning.





E27 PENDANT LAMP - EU VERSION




















LAMP RATING

 Voltage
 22O-24OV

 Frequency
 5OHz

 IP Rating
 P2O

 Classification
 Class II

 Socket
 I x E27

Max. 6W; LED bulb

BULB RECOMMENDATION

Lamp baseE27DimensionsØ125 X 175 mmLight source shapeG125Max wattage6WLight source typeLED

BULB SPECIFICATION

Item GI25 LED filament bulb

 Watt
 2 W

 Lumen
 >8Olm/W

 Kelvin
 25OOK

 Lifetime
 25.0OOh

 CRI
 ≥9O

 Dimmable
 Yes

GENERAL STANDARDS & CERTIFICATES

EU CHINA
REACH CCC

Directive - EC/1907/2006 GB 7000.201 and GB 7000.1

Low Voltage Directive (LVD)- 2014/35/EU IEC 60598-I and IEC 60598-2-I (EU deviations)

ROHS Directive - 2011/65/EU amended RoHS 3 Directive 2015/863

ECO Design Directive - 245/2009/EC

WEEE Directive - 2012/19/EU

kWh/1000h

UK

BS EN 60598-I and BS 4533-IO2.I, EN 60598-2-I

Electrical Equipment (Safety) Regulations 2016

Electromagnetic Compatibility Regulations 2016

The Restriction of the Use of Certain Hazardous Substances in Electrical and

Electronic Equipment Regulations 2012

The Ecodesign for Energy-Related Products and Energy Information

(Amendment) (EU Exit) Regulations 2019