CANDY DYE YELLOW

Compilation date: 01/02/2015

Revision date: 16/02/2022

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: CANDY DYE YELLOW

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: CREATIVE PAINT LTD

24/6 DRYDEN ROAD BILSTON GLEN IND. EST. LOANHEAD MIDLOTHIAN EH20 9HX

Email: Hello@creativepaints.co.uk

1.4. Emergency telephone number

Emergency tel: 0131 440 9804 (Main Telephone number)

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 3: H226; Skin Irrit. 2: H315; Acute Tox. 4: H332; -: EUH208

Most important adverse effects: Contains 2, 3-epoxypropyl neodecanate. May produce an allergic reaction. Flammable

liquid and vapour. Causes skin irritation. Harmful if inhaled.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains 2, 3-epoxypropyl neodecanate. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H315: Causes skin irritation.

H332: Harmful if inhaled.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



CANDY DYE YELLOW

| Signal words: | Warning |
|---------------------------|----------------------------------------------------------------------------------------|
| Precautionary statements: | P102: Keep out of reach of children. |
| | P264: Wash hands thoroughly after handling. |
| | P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition |
| | sources. No smoking. |
| | P233: Keep container tightly closed. |
| | P240: Ground/Bond container and receiving equipment. |
| | P241: Use explosion-proof electrical/ventilating/lighting/ equipment. |
| | P242: Use only non-sparking tools. |
| | P243: Take precautionary measures against static discharge. |
| | P260: Do not breathe dust/fumes/gas/mist/vapours/spray. |
| | P271: Use only outdoors or in a well-ventilated area. |
| | P280: Wear protective gloves/protective clothing/eye protection/face protection. |
| | P302+352: IF ON SKIN: Wash with plenty of water/. |
| | P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. |
| | Rinse skin with. |
| | P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| | P312: Call a if you feel unwell. |
| | P332+313: If skin irritation occurs: Get medical advice/attention. |
| | P362: Take off contaminated clothing. |
| | P370+378: In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to |
| | extinguish. |
| | P403+235: Store in a well-ventilated place. Keep cool. |
| | P501: Dispose of contents/container to hazardous waste according to local and regional |
| | regulations. |
| 2.3. Other hazards | |

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

CYCLOHEXANONE

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|-----------|----------|-----------|----------------------------------------|---------|
| 203-631-1 | 108-94-1 | - | Flam. Liq. 3: H226; Acute Tox. 4: H332 | 30-50% |

Page: 2

CANDY DYE YELLOW

Page: 3

| XYLENE | | | | | |
|-------------------------------------------------------------------------------------|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|--------|--|
| 215-535-7 1330 | 0-20-7 | - | Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315 | 10-30% | |
| N-BUTYL ACETATE | | | | | |
| 204-658-1 123- | -86-4 | - | Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066 | 1-10% | |
| 1-METHOXY-2-PROP | ANOL | | | | |
| 203-539-1 107- | -98-2 | - | Flam. Liq. 3: H226; STOT SE 3: H336 | 1-10% | |
| 2-METHOXY-1-METH | IYLETHYL | ACETATE | | | |
| 203-603-9 108- | -65-6 | Substance with a Community workplace exposure limit. | Flam. Liq. 3: H226 | 1-10% | |
| 2, 3-EPOXYPROPYL | NEODEC | ANATE | | | |
| | 61-45-5 -979-2 | - | Skin Sens. 1: H317; Muta. 2: H341; Aquatic Chronic 2: H411 | <1% | |
| ion 4: First aid mea | asures | | | | |
| 1. Description of first | t aid meas | sures | | | |
| | | | | - 1- | |
| SKINC | | Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Do not use solvents or thinners. Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Remove any contact lenses. Consult a doctor. Consult a doctor. Do not induce vomiting. Keep at rest. Move to fresh air in case of accidental inhalation of vapours. Keep patient warm and at | | | |
| Eve e | | | | | |
| Eye C | | | | | |
| Ing | | | | | |
| | | | | | |
| | | rest. If unconscious, check for breathing and apply artificial respiration if necessary. If | | | |
| | | unconscious place in recovery position and seek medical advice. | | | |
| 2. Most important sv | | and effects, both acute and delayed | | | |
| | | | | | |
| Skind | | Repeated or prolonged contact with the mixture may cause removal of natural fat from | | | |
| | | the skin resulting in desiccation of the skin. The product may be absorbed through the | | | |
| skin. Indication of any immediate medical attention and special treatment needed | | | | | |
| | mineulate | medical attention and special frea | | | |
| ion 5: Fire-fighting | measur | es | | | |
| 1. Extinguishing med | dia | | | | |
| Extinguishing | media: \ | Water spray. Alcohol resistant foam. I | Dry chemical. Carbon dioxide. Use water spray | to | |
| | | cool containers. Do not use water jet. | | | |
| 2. Special hazards ar | rising fror | n the substance or mixture | | | |
| Exposure ha | azards: / | As the product contains combustible of | organic components, fire will product dense bla | ck | |

smoke containing hazardous products of combustion. Exposure to decomposition

CANDY DYE YELLOW

products may be a hazard to health. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

Section 6: Accidental release measures

| 6.1. Personal precautions, protective equipment and emergency procedures | | | | | | |
|---------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|--|--|--|--|--|
| Personal precautions: Solvent vapours are heavier than air and may spread along floors. Ensure adequate | | | | | | |
| | ventilation. Wear a mask, gloves and protective clothing. Evacuate the area immediately. | | | | | |
| Keep people away from and upwind of spill/leak. | | | | | | |
| 6.2. Environmental precaution | 6.2. Environmental precautions | | | | | |
| Environmental precautions: | Do not allow to enter sewers/surface or ground water. Inform respective authorities in | | | | | |
| case of seepage into water course or sewage system. | | | | | | |
| 6.3. Methods and material for containment and cleaning up | | | | | | |

ods and material for containment and cleaning up

Clean-up procedures: Clean with detergents. Avoid solvents. Contain spillage. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Clean contaminated surface thoroughly. Dispose of as hazardous waste.

6.4. Reference to other sections

Reference to other sections: Refer to section 15.

Section 7: Handling and storage

7.1. Precautions for safe handling

| Handling requirements: | Avoid exceeding exposure limits. Ensure there is exhaust ventilation of the area. Earth | | | |
|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|
| | any equipment used in handling. Do not eat or drink in work area. Avoid contact with | | | |
| | skin, eyes and clothing. Avoid contact and inhalation of vapours. Thoroughly mix before | | | |
| | use. After use, store in a well-sealed container. Prevent the formation of flammable or | | | |
| | explosive concentrations of vapour in air. This product should only be used in areas from | | | |
| | which all naked lights and other sources of ignition have been excluded. | | | |
| 7.2. Conditions for safe storag | e, including any incompatibilities | | | |
| Storage conditions: Store in a cool, well ventilated area. Ensure lighting and electrical equipment are r | | | | |
| Storage conditions: | Store in a cool, well ventilated area. Ensure lighting and electrical equipment are not a | | | |
| Storage conditions: | Store in a cool, well ventilated area. Ensure lighting and electrical equipment are not a source of ignition. Keep away from direct sunlight. Keep away from sources of ignition. | | | |
| Storage conditions: | | | | |

7.3. Specific end use(s)

Specific end use(s): Paints, varnishes and enamels. Coloured clearcoat.

Page: 4

CANDY DYE YELLOW

Page: 5

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

CYCLOHEXANONE

Workplace exposure limits: Respirable dust State 8 hour TWA 15 min. STEL 8 hour TWA 15 min. STEL UK 10 ppm 20 ppm --**XYLENE** UK 220 mg/m3 441 mg/m3 --**N-BUTYL ACETATE** UK 724 mg/m3 966 mg/m3 --1-METHOXY-2-PROPANOL UK 375 mg/m3 560 mg/m3 -_ 2-METHOXY-1-METHYLETHYL ACETATE UK 274 mg/m3 548 mg/m3 --

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

| | Engineering measures: | Ensure there is exhaust ventilation of the area. Ensure lighting and electrical equipment |
|----------------------------------------------------------------------------------------------|-------------------------|-------------------------------------------------------------------------------------------|
| | | are not a source of ignition. |
| | Respiratory protection: | Respirator with combination filter for vapour/particulate (EN 141). |
| Hand protection: Protective gloves. Ensure gloves are manufactured/tested in accordance with | | Protective gloves. Ensure gloves are manufactured/tested in accordance with BS EN |
| | | 374. Wash hands after use. |
| | Eye protection: | Safety glasses with side-shields. Chemical resistant goggles. |
| | Skin protection: | Protective clothing. Antistatic boots. |
| | Environmental: | Prevent from entering in public sewers or the immediate environment. |

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Indigo blue

Odour: Solvent like.

Flash point°C: >23 - 55

9.2. Other information

Other information: No data available.

CANDY DYE YELLOW

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Oxidising agents. Strong alkalis. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide. In combustion emits toxic fumes of carbon monoxide. In combustion emits toxic fumes of nitrogen oxides. Emits dense black smoke.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

CYCLOHEXANONE

| ORL | MUS | LD50 | 1400 | mg/kg |
|-----|-----|------|------|-------|
| ORL | RAT | LD50 | 1620 | µl/kg |
| SCU | RAT | LD50 | 2170 | mg/kg |

XYLENE

| ORL | MUS | LD50 | 2119 | mg/kg |
|-----|-----|------|------|-------|
| ORL | RAT | LD50 | 4300 | mg/kg |
| SCU | RAT | LD50 | 1700 | mg/kg |

N-BUTYL ACETATE

| ORL | MUS | LD50 | 6 | gm/kg |
|-----|-----|------|-------|-------|
| ORL | RAT | LD50 | 10768 | mg/kg |

CANDY DYE YELLOW

Page: 7

1-METHOXY-2-PROPANOL

| IVN | RAT | LD50 | 4200 | mg/kg |
|-----|-----|------|-------|-------|
| ORL | MUS | LD50 | 11700 | mg/kg |
| ORL | RAT | LDLO | 3739 | mg/kg |

2-METHOXY-1-METHYLETHYL ACETATE

| IPR | MUS | LD50 | 750 | mg/kg |
|-----|-----|------|------|-------|
| ORL | RAT | LD50 | 8532 | mg/kg |

Relevant hazards for product:

| Hazard | Route | Basis |
|-----------------------------|-------|-----------------------|
| Acute toxicity (ac. tox. 4) | INH | Hazardous: calculated |
| Skin corrosion/irritation | DRM | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: Repeated or prolonged contact with the mixture may cause removal of natural fat from

the skin resulting in desiccation of the skin. The product may be absorbed through the

skin.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: This product contains substances dangerous to the environment. (See section 3).

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: This product should not be allowed to enter drains, water courses or the soil. Must not

be disposed together with household waste. Dispose of waste and residues in

accordance with local and regional regulations.

CANDY DYE YELLOW

NB: The user's attention is drawn to the possible existence of regional or national

Marine pollutant: No

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: |||

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

| Other information: | This safety data sheet is prepared in accordance with Commission Regulation (EU) No |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| | 2015/830. |
| | * indicates text in the SDS which has changed since the last revision. |
| Phrases used in s.2 and s.3: | EUH066: Repeated exposure may cause skin dryness or cracking. |
| | EUH208: Contains <name of="" sensitising="" substance="">. May produce an allergic reaction.</name> |
| | H226: Flammable liquid and vapour. |
| | H312: Harmful in contact with skin. |
| | H315: Causes skin irritation. |
| | H317: May cause an allergic skin reaction. |
| | H332: Harmful if inhaled. |
| | H336: May cause drowsiness or dizziness. |
| | H341: Suspected of causing genetic defects <state conclusively<="" exposure="" if="" is="" it="" of="" route="" th=""></state> |
| | proven that no other routes of exposure cause the hazard>. |
| | H411: Toxic to aquatic life with long lasting effects. |

CANDY DYE YELLOW

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[final page]

Page: 9