

# SAFETY DATA SHEET

CHROMIUM

Compilation date: 06/10/2015

Revision date: 16/02/2022

Revision No: 2

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product name: CHROMIUM

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.3. Details of the supplier of the safety data sheet

Company name: CREATIVE PAINT LTD

24/6 DRYDEN ROAD  
BILSTON GLEN IND. EST.  
LOANHEAD  
MIDLOTHIAN  
EH20 9HX

Email: Hello@creativepaints.co.uk

### 1.4. Emergency telephone number

Emergency tel: 0131 440 9804 (Main Telephone number)  
(office hours only)

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification under CLP: STOT SE 3: H336; Eye Irrit. 2: H319; Flam. Liq. 2: H225; Skin Sens. 1: H317

Most important adverse effects: Highly flammable liquid and vapour. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.

### 2.2. Label elements

Label elements:

Hazard statements: H225: Highly flammable liquid and vapour.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



[cont...]

# SAFETY DATA SHEET

## CHROMIUM

Page: 2

**Signal words:** Danger

**Precautionary statements:** P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233: Keep container tightly closed.

P240: Ground/Bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a if you feel unwell.

P321: Specific treatment (see instructions on this label).

P333+313: If skin irritation or rash occurs: Get medical advice/attention.

P337+313: If eye irritation persists: Get medical advice/attention.

P363: Wash contaminated clothing before reuse.

P370+378: In case of fire: Use dry sand to extinguish.

P501: Dispose of contents/container to hazardous waste collection point.

### 2.3. Other hazards

**Other hazards:** Highly flammable.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

PROPAN-2-OL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	70-90%

[cont...]

# SAFETY DATA SHEET

## CHROMIUM

Page: 3

### ACETONE

200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	---------	---	---	-------

### ETHYL ACRYLATE

205-438-8	140-88-5	-	Flam. Liq. 2: H225; Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317	1-10%
-----------	----------	---	---	-------

### ISOPROPYL ACETATE

203-561-1	108-21-4	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	----------	---	---	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

### 4.2. Most important symptoms and effects, both acute and delayed

### 4.3. Indication of any immediate medical attention and special treatment needed

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

### 5.2. Special hazards arising from the substance or mixture

### 5.3. Advice for fire-fighters

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

### 6.2. Environmental precautions

### 6.3. Methods and material for containment and cleaning up

### 6.4. Reference to other sections

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

### 7.2. Conditions for safe storage, including any incompatibilities

### 7.3. Specific end use(s)

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

[cont...]

# SAFETY DATA SHEET

## CHROMIUM

### Hazardous ingredients:

#### PROPAN-2-OL

##### Workplace exposure limits:

##### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	999 mg/m <sup>3</sup>	1250 mg/m <sup>3</sup>	-	-

#### ACETONE

UK	1210 mg/m <sup>3</sup>	3620 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

#### ETHYL ACRYLATE

UK	21 mg/m <sup>3</sup>	42 mg/m <sup>3</sup>	-	-
----	----------------------	----------------------	---	---

#### ISOPROPYL ACETATE

UK	420 mg/m <sup>3</sup>	849 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

### DNEL/PNEC Values

DNEL / PNEC No data available.

### 8.2. Exposure controls

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Silver

**Odour:** Characteristic odour

**Flash point°C:** <23

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

### 10.2. Chemical stability

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

## Section 11: Toxicological information

# SAFETY DATA SHEET

## CHROMIUM

Page: 5

### 11.1. Information on toxicological effects

#### Hazardous ingredients:

##### PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

##### ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

##### ETHYL ACRYLATE

ORL	MUS	LD50	1799	mg/kg
ORL	RAT	LD50	800	mg/kg
SKN	RAT	LDLO	1800	mg/kg

##### ISOPROPYL ACETATE

IVN	RAT	LDLO	174	mg/kg
ORL	RAT	LD50	6750	mg/kg

#### Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

### Symptoms / routes of exposure

## Section 12: Ecological information

### 12.1. Toxicity

#### Hazardous ingredients:

##### ACETONE

BLUEGILL (Lepomis macrochirus)	LC50	8300	mg/l
--------------------------------	------	------	------

### 12.2. Persistence and degradability

[cont...]

# SAFETY DATA SHEET

CHROMIUM

Page: 6

## 12.3. Bioaccumulative potential

## 12.4. Mobility in soil

## 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

## 12.6. Other adverse effects

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1993

### 14.2. UN proper shipping name

**Shipping name:** FLAMMABLE LIQUID, N.O.S.  
(PROPAN-2-OL)

### 14.3. Transport hazard class(es)

**Transport class:** 3

### 14.4. Packing group

**Packing group:** II

### 14.5. Environmental hazards

**Environmentally hazardous:** No

**Marine pollutant:** No

### 14.6. Special precautions for user

**Tunnel code:** D/E

**Transport category:** 2

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

[cont...]

## SAFETY DATA SHEET

### CHROMIUM

Page: 7

**Phrases used in s.2 and s.3:** EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.