

SAFETY DATA SHEET
WET LOOK CLEAR COAT SPRAY CAN 2K

Compilation date: 17/05/2016

Revision date: 16/02/2022

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: WET LOOK CLEAR COAT SPRAY CAN 2K

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: CREATIVE PAINTS LTD

24/6 DRYDEN ROAD
BILSTON GLEN IND. EST.
LOANHEAD
MIDLOTHIAN
EH20 9HX

Email: [Hello@creativepaints.co.uk](mailto>Hello@creativepaints.co.uk)

1.4. Emergency telephone number

Emergency tel: 0131 440 9804 (Main Telephone number)
(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Aerosol 1: H222; Eye Irrit. 2: H319; Skin Sens. 1: H317; STOT SE 3: H336; -: EUH208; -: H229

Most important adverse effects: Contains mixture of alpha-3-(3-(2h-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2h-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) and alpha-3-(3-(2h-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propio. May produce an allergic reaction. Extremely flammable aerosol. Pressurised container: May burst if heated. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains mixture of alpha-3-(3-(2h-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2h-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) and alpha-3-(3-(2h-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propio. May produce an allergic reaction.

[cont...]

SAFETY DATA SHEET

WET LOOK CLEAR COAT SPRAY CAN 2K

Page: 2

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a if you feel unwell.

P333+313: If skin irritation or rash occurs: Get medical advice/attention.

P337+313: If eye irritation persists: Get medical advice/attention.

P363: Wash contaminated clothing before reuse.

P403+233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501: Dispose of contents/container to waste according to local/regional regulations.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

[cont...]

SAFETY DATA SHEET
WET LOOK CLEAR COAT SPRAY CAN 2K

Page: 3

Hazardous ingredients:

DIMETHYL ETHER

EINECS	CAS	PBT / WEL	CLP Classification	Percent
204-065-8	115-10-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	30-50%

ACETONE

200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	10-30%
-----------	---------	---	--	--------

N-BUTYL ACETATE

204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	10-30%
-----------	----------	---	--	--------

ALIPHATIC POLYCYANATE

-	28182-81-2	-	Acute Tox. 4: H302+312+332; Skin Sens. 1: H317; STOT SE 3: H335; STOT SE 3: H336	1-10%
---	------------	---	--	-------

XYLENE

215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1-10%
-----------	-----------	---	---	-------

2-METHOXY-1-METHYLETHYL ACETATE

203-603-9	108-65-6	Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226	1-10%
-----------	----------	--	--------------------	-------

BUTAN-1-OL

200-751-6	71-36-3	-	Flam. Liq. 3: H226; Acute Tox. 4: H302; STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318; STOT SE 3: H336	1-10%
-----------	---------	---	---	-------

MIXTURE OF ALPHA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYL-OMEGA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIONYLOXYPOLY(OXYETHYLENE) AND ALPHA-3-(3-(2H-BENZOTRIAZOL-2-YL)-5-TERT-BUTYL-4-HYDROXYPHENYL)PROPIO

400-830-7	-	-	Skin Sens. 1: H317; Aquatic Chronic 2: H411	<1%
-----------	---	---	---	-----

Section 4: First aid measures

4.1. Description of first aid measures

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

[cont...]

SAFETY DATA SHEET
WET LOOK CLEAR COAT SPRAY CAN 2K

Page: 4

5.2. Special hazards arising from the substance or mixture

5.3. Advice for fire-fighters

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

7.2. Conditions for safe storage, including any incompatibilities

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DIMETHYL ETHER

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	766 mg/m ³	958 mg/m ³	-	-

ACETONE

UK	1210 mg/m ³	3620 mg/m ³	-	-
----	------------------------	------------------------	---	---

N-BUTYL ACETATE

UK	724 mg/m ³	966 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

XYLENE

UK	220 mg/m ³	441 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

2-METHOXY-1-METHYLETHYL ACETATE

UK	274 mg/m ³	548 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

BUTAN-1-OL

UK	-	154 mg/m ³	-	-
----	---	-----------------------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

[cont...]

SAFETY DATA SHEET
WET LOOK CLEAR COAT SPRAY CAN 2K

Page: 5

8.2. Exposure controls

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Colourless

Odour: Characteristic odour

Flash point°C: <1

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

10.5. Incompatible materials

10.6. Hazardous decomposition products

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

N-BUTYL ACETATE

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg

[cont...]

SAFETY DATA SHEET
WET LOOK CLEAR COAT SPRAY CAN 2K

Page: 6

SCU	RAT	LD50	1700	mg/kg
-----	-----	------	------	-------

2-METHOXY-1-METHYLETHYL ACETATE

IPR	MUS	LD50	750	mg/kg
ORL	RAT	LD50	8532	mg/kg

BUTAN-1-OL

IVN	RAT	LD50	310	mg/kg
ORL	MUS	LD50	2680	mg/kg
ORL	RAT	LD50	790	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

ACETONE

BLUEGILL (Lepomis macrochirus)	LC50	8300	mg/l
--------------------------------	------	------	------

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

[cont...]

SAFETY DATA SHEET
WET LOOK CLEAR COAT SPRAY CAN 2K

Page: 7

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Tunnel code: D

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.
EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.
H220: Extremely flammable gas.
H222: Extremely flammable aerosol.
H225: Highly flammable liquid and vapour.
H226: Flammable liquid and vapour.
H229: Pressurised container: May burst if heated
H302: Harmful if swallowed.
H302+312+332: Harmful if swallowed, in contact with skin or if inhaled.
H312: Harmful in contact with skin.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.

[cont...]

SAFETY DATA SHEET
WET LOOK CLEAR COAT SPRAY CAN 2K

Page: 8

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.