

Tactile™

Technical data sheet

Tactile™ is a soft touch paint provided in a convenient 2K-spray can; this coating, when applied, produces a soft rubbery surface.

The coating dries to a slight semi-opaque finish and is best applied over a fully cured 2k primer; our 2k primer spray cans are ideal; these are available from our web-shop.

Alternatively, Tactile can be applied directly to a coloured automotive 2 stage basecoat; there is no need to abrade the basecoat as long as Tactile has been applied within the 8 hours basecoat time window.

1. To activate the product, remove the plastic cover from the base of the can to reveal the metal pull ring inside the cover.
2. Attach the pull ring to the pin that's situated on the bottom of the can; ensuring you fully pull up the ring and twist a full 360 degrees to release the built-in curing agent.

(Ensure the ring has been fully pulled and twisted the full 360 degrees; otherwise, the curing agent will not be fully released, and your item will not dry correctly!)

3. Shake the aerosol can for at least two minutes after the agitator ball has been released. Your spray can has now been fully activated and is ready for use.

The paint within the can will have a usable pot life of 8 hours before it sets within the spray can.

4. Apply a wet coat from a distance of 10-12 inches with a 50% overlap to ensure an even film build. If another coat is required, a flash off time of 30mins at 19C is required. The more layers that are applied, the more rubbery the surface will be. We find two full coats are adequate for a soft tactile finish.

5. Drying time on this product is slightly longer than conventional 2 part paints due to the product's chemical makeup, touch dry is up to 12 hours, full properties are achieved after a full seven days at 20C.

HEALTH & SAFETY

Please read all Material Safety Data Sheets for all products before use.

Due to the inability of Creative Paints Ltd to anticipate or control conditions whereby our products will be employed, Creative Paints Ltd does not represent or guarantee that any Creative Paints Ltd product is fit for a particular purpose. Our products should be tested by users to determine suitability for a particular purpose. We disclaim responsibility for claims and damages beyond replacement of any defective of our product. There are no warranties which extend beyond the description on the face here of.

Updated: 16/02/2022