



# HYDROTAP G5 BHA CELSIUS ARC BRUSHED NICKEL



BOILING



HOT & AMBIENT

FILTERED

UNFILTERED



## Order Code H58786Z11AU

Zip HydroTap Design Range CELSIUS Boiling Filtered water, plus Hot and Cold washing up water from a single tap. The system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 3 energy saving modes including ON/OFF timers and 2 hour sleep mode, antimicrobial protection impregnated into key water paths for enhanced hygiene, and 0.2 micron water filtration.

Manufacturing Code H58786Z11AU

Capacity Residential

Tap Zip HydroTap Design Range CELSIUS ARC Tap (Brushed Nickel)

Water Pressure Min 170kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold and Hot

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 1.35kW 220-240V 50Hz

Power Supply 1 x 10 Amp socket outlet

Dimensions W280mm x D313mm x H333mm

Product Approvals WaterMark, RCM

Wels Rating 5 Star, 5.5 litres

## Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.
3. Zip Micro is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com/book-service-visit](http://www.zipwater.com/book-service-visit)

## Installation Detail

EPK2 HydroTap G5 v1.00 02.21 B, BA

Ventilation requirements <small>Contact your local service provider if ventilation is not suitable</small>		HydroTap Tap options	
<p><b>Clearance envelope</b> Position the Tap and the Command Centre as close together as possible.</p>		<p><b>Celsius Arc Tap</b></p>	
<p><b>Tap Positioning</b> Position the Tap to dispense into the sink, allowing clearance for a cup or teapot.</p>		<p><b>Celsius Cube Tap</b></p>	
<p><b>Air outlet louvre (if required)</b> Cut-out in door/wall, towards the top of the cabinet</p> <p><b>Air inlet cut-out (required)</b> Cut-out in cabinet floor</p>		<p><b>Mains hot water supply installation</b> Hot and cold water supply required</p>	
<p><b>Clearance Envelope</b> Position the Tap to dispense into the sink, allowing clearance for a cup or teapot.</p>		<p><b>Clearance Envelope</b></p> <p><b>Booster (B100 models)</b> NOTE: Not shown to scale. The 800mm hoses supplied with the Booster cannot be lengthened</p>	
<p><b>Mains cold water isolation valve (not supplied)</b></p> <p><b>Air inlet grille</b></p> <p><b>IEC Flex &amp; Plug 230-240V, 50Hz power outlet</b></p>		<p><b>Booster (B100 models)</b> NOTE: Not shown to scale. The 800mm hoses supplied with the Booster cannot be lengthened</p>	

SCALE 1:5  
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

# HydroTap G5

## B Home, B60, B100

shown with Celsius Arc Tap