



# HYDROTAP G5 BC CUBE PLUS GUNMETAL



BOILING

CHILLED

FILTERED

## Order Code H5C784Z09AU

Zip HydroTap Design Range Boiling, Chilled, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 3 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration.



Manufacturing Code H5C784Z09AU

Capacity Residential

Tap Zip HydroTap Design Range CUBE Plus Tap (Gunmetal)

Water Pressure Min 170kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 1.44kW 220-240V 50Hz

Power Supply 1 x 10 Amp socket outlet

Dimensions W280mm x D455mm x H333mm

Product Approvals WaterMark, RCM, ARC

Warranty 5 years (appliance warranty 36 months plus additional 24 months tank warranty)

# Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.
3. Zip Micro is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com/book-service-visit](http://www.zipwater.com/book-service-visit)

## Installation Detail

BKL2 HydroTap G5 v1.10 07.04 BC BC20

**Ventilation requirements** Contact your local service provider if ventilation is not suitable

**Clearance envelope**  
Position the Tap and the Command Centre as close together as possible.

200  
333  
50  
Command Centre width

**HydroTap Tap options**

**HydroTap Arc Plus Tap**

30 162 232 134 387 87 45 54

**HydroTap Cube Plus Tap**

30 162 217 134 349 87 45 54

**Standalone Font with Arc Plus Tap**

162 232 174 387 54 140 176

**Cutting detail**  
174 for HydroTap Arc/Cube  
3-off Ø10 holes @ 155mm PCD, equispaced  
Ø140 hole for bowl  
Ø176 outline of Font  
Ø35 hole for tap

**Tap Positioning**  
Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount on a Font (available as an accessory).

Ø35mm hole for HydroTap Plus Tap  
4mm buffer pad air space

**Tap Positioning**  
Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount on a Font (available as an accessory).

200 min.  
333  
50 min.  
280  
50 min.  
Clearance Envelope  
HydroTap Arc Plus  
Mains cold water isolation valve (not supplied)  
Air inlet grille  
IEC Flex & Plug 230-240V, 50Hz power outlet  
455

**HydroTap G5**  
**BC Home, BC20**  
shown with HydroTap Arc Plus

SCALE 1:5  
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.