

HYDROTAP G5 BA CUBE PLUS BRUSHED CHROME





BOILING

AMBIENT

FILTERED

Order Code H5C785Z01AU

Zip HydroTap Design Range Boiling, Ambient, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 3 energy saving modes including ON/OFF timers and 2 hour sleep mode, antimicrobial protection impregnated into key water paths for enhanced hygiene, and 0.2 micron water filtration.





| Тар | Zip HydroTap Design Range CUBE Plus Tap (Brushed Chrome) |
|------------------------------|--|
| Water Pressure | Min 170kPa - Max 700kPa |
| Water Connection | 1/2" BSP (G1/2) |
| Water Supply Requirements | Cold |
| Water Valves | Integrated 500kPa Pressure limiting valve and Dual Check Valve |
| Power Rating | 1.35kW 220-240V 50Hz |
| Power Supply | 1 x 10 Amp socket outlet |
| Dimensions | W280mm x D313mm x H333mm |
| Product Approvals | WaterMark, RCM |
| Warranty | 5 years (appliance warranty 36 months plus additional 24 months tank warranty) |

Installation Requirements

- 1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
- 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.
- 3. Zip Micro is air-cooled so discrete cabinetry cut-outs are required for ventilation.
- 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
- 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.

ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED

6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com/book-service-visit

Installation Detail Ventilation requirements contact your local so HydroTap Tap options Clearance envelope HydroTap Arc Plus Tap Standalone Font Position the Tap and the Command Centre as close together as possible. 200 333 HydroTap Cube Plus Tap **Cutting detail** Air outlet louvre (if required) Cut-out in door/wall, towards the top of the cabinet **Tap Positioning** Position the Tap to dispense into the sink allowing clearance for a cup or teapot. Alternatively, mount on a Font 4mm buffer pad air space Ø35mm hole for HydroTap Arc Plus 333 **HydroTap G5** B Home, B60, B100 Air inlet grille IEC Flex & Plug 230-240V, 50Hz BA Home, BA60, BA100 shown with HydroTap Arc Plus