

HYDROTAP G5 CS CUBE PLUS GUNMETAL





CHILLED

SPARKLING

FILTERED

Order Code H5C787Z09AU

Zip HydroTap Design Range Chilled, Sparkling, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 3 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and 2 disposable CO2 cylinders.

Manufacturing Code	H5C787Z09AU
Capacity	Residential



Water Pressure Min 250kPa - Max 700kPa Water Connection 1/2" BSP (G1/2) Water Supply Requirements Cold
Water Supply Cold
Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating 0.18kW 220-240V 50Hz
Power Supply 1 x 10 Amp socket outlet
Dimensions W280mm x D406mm x H333mm
Product Approvals WaterMark, RCM, ARC
Warranty 5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

Installation Detail

200 min.

333

50 min.

INS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED

- 1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
- 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.
- 3. Zip Micro is air-cooled so discrete cabinetry cut-outs are required for ventilation.
- 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
- 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
- 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com/book-service-visit

HydroTap Tap options

Ventilation requirements Contact your local service pro HydroTap Arc Tap Standalone Font Position the Tap and the Com as close together as possible 200 53 Ø40 333 HydroTap Cube Tap Ø140 Air outlet louvre (if required) Cut-out in door/wall, towards the top of the cabinet 276 - 326 Air inlet cut-out (required) **Tap Positioning** HydroTap Arc

HydroTap G5 CS Home

shown with HydroTap Arc