

HYDROTAP G5 C CUBE PLUS GUNMETAL



FILTERED

Order Code H5C788Z09AU

Zip HydroTap Design Range Chilled, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 3 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration.

Manufacturing Code	H5C788Z09AU
Capacity	Residential



Тар	Zip HydroTap Design Range CUBE Plus Tap (Gunmetal)
Water Pressure	Min 170kPa - Max 700kPa
Water Connection	1/2" BSP (G1/2)
Water Supply Requirements	Cold
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	0.17kW 220-240V 50Hz
Power Supply	1 x 10 Amp socket outlet
Dimensions	W280mm x D406mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

- 1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
- 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.
- 3. Zip Micro is air-cooled so discrete cabinetry cut-outs are required for ventilation.
- 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
- 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.

ONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED

6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com/book-service-visit

Installation Detail Ventilation requirements Contact your local service prov HydroTap Tap options HydroTap Arc Plus Tap Standalone Font Position the Tap and the Comma as close together as possible. with Arc Plus Tap 200 33 333 HydroTap Cube Plus Tap Ø176 Air outlet louvre (if required) Cut-out in door/wall, towards the top of the cabinet Ø 140 hole for bowl Air inlet cut-out (required) 300 **Tap Positioning** 200 min. 333 **HydroTap G5** C Home Air inlet grille \ IEC Flex & Plug 230-240V, 50Hz __ 50 min. shown with HydroTap Arc Plus SCALE 1:5 ALL DIMEN