

HYDROTAP G5 C ELITE PLUS MATTE BLACK



FILTERED

Order Code H5E788Z03AU

Zip HydroTap Design Range Chilled, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration.

Manufacturing Code	H5E788Z03AU
Capacity	Residential



Тар	Zip HydroTap Design Range ELITE PLUS Tap (Matte Black)
Water Pressure	Min 250kPa - Max 700kPa
Water Connection	1/2" BSP (G1/2)
Water Supply Requirements	Cold
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	0.17kW 220-240V 50Hz
Power Supply	1 x 10 Amp socket outlet
Dimensions	W280mm x D406mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

- 1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
- 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.
- 3. Zip Micro is air-cooled so discrete cabinetry cut-outs are required for ventilation.
- 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
- 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
- 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com/book-service-visit

Installation Detail Ventilation requirements Contact your local service provider if w HydroTap Tap options Font options Raised Font Font Position the Tap and the Comm as close together as possible. 200 333 Tap Positioning **Cutting detail** Ø 108 **Cutting detail** HydroTap Tap Air inlet cut-out (required) Cut-out in cabinet floor 326 Clearance 200 min. 333 HydroTap G5 C Home Air inlet grille IEC Flex & Plug 230-240V, 50Hz shown with "Classic Plus" Tap SCALE 1:5 ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY, HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.