

HYDROTAP G5 C ELITE PLUS BRUSHED ROSE GOLD



FILTERED

Order Code H5E788Z05AU

Zip HydroTap Design Range Chilled, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration.

Manufacturing Code	H5E788Z05AU
Capacity	Residential



Tap Zip HydroTap Design Range ELITE PLUS Tap (Brushed Rose Gold) Water Pressure Min 250kPa - Max 700kPa Water Connection 1/2" BSP (G1/2) Water Supply Requirements Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve Power Rating 0.17kW 220-240V 50Hz Power Supply 1 x 10 Amp socket outlet Dimensions W280mm x D406mm x H333mm Product Approvals WaterMark, RCM, ARC Warranty 5 years (appliance warranty 36 months plus additional 24 months tank warranty)		
Water Connection 1/2" BSP (G1/2) Water Supply Requirements Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve Power Rating 0.17kW 220-240V 50Hz Power Supply 1 x 10 Amp socket outlet Dimensions W280mm x D406mm x H333mm Product Approvals WaterMark, RCM, ARC	Тар	Zip HydroTap Design Range ELITE PLUS Tap (Brushed Rose Gold)
Water Supply Requirements Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve Power Rating 0.17kW 220-240V 50Hz Power Supply 1 x 10 Amp socket outlet Dimensions W280mm x D406mm x H333mm Product Approvals WaterMark, RCM, ARC	Water Pressure	Min 250kPa - Max 700kPa
Requirements Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve Power Rating 0.17kW 220-240V 50Hz Power Supply 1 x 10 Amp socket outlet Dimensions W280mm x D406mm x H333mm Product Approvals WaterMark, RCM, ARC	Water Connection	1/2" BSP (G1/2)
Power Rating 0.17kW 220-240V 50Hz Power Supply 1 x 10 Amp socket outlet Dimensions W280mm x D406mm x H333mm Product Approvals WaterMark, RCM, ARC		Cold
Power Supply 1 x 10 Amp socket outlet Dimensions W280mm x D406mm x H333mm Product Approvals WaterMark, RCM, ARC	Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Dimensions W280mm x D406mm x H333mm Product Approvals WaterMark, RCM, ARC	Power Rating	0.17kW 220-240V 50Hz
Product Approvals WaterMark, RCM, ARC	Power Supply	1 x 10 Amp socket outlet
	Dimensions	W280mm x D406mm x H333mm
Warranty 5 years (appliance warranty 36 months plus additional 24 months tank warranty)	Product Approvals	WaterMark, RCM, ARC
	Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

- 1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
- 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.
- 3. Zip Micro is air-cooled so discrete cabinetry cut-outs are required for ventilation.
- 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
- 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
- 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com/book-service-visit

Installation Detail

