



HYDROTAP G5 C ELITE PLUS BRUSHED NICKEL



CHILLED

FILTERED

Order Code H5E788Z11AU

Zip HydroTap Design Range Chilled, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration.



Manufacturing Code H5E788Z11AU

Capacity Residential

Tap Zip HydroTap Design Range ELITE PLUS Tap (Brushed Nickel)

Water Pressure Min 250kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 0.17kW 220-240V 50Hz

Power Supply 1 x 10 Amp socket outlet

Dimensions W280mm x D406mm x H333mm

Product Approvals WaterMark, RCM, ARC












Warranty 5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.
3. Zip Micro is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com/book-service-visit

Installation Detail

BKL2 HydroTap G5 v1.00 02.21

Ventilation requirements <small>Contact your local service provider if ventilation is not suitable</small>		HydroTap Tap options	Font options
Clearance envelope Position the Tap and the Command Centre as close together as possible. 		Classic Plus  Elite Plus 	Raised Font with 135mm Extension  Font with 135mm Extension 
 <p>Air outlet louvre (if required) Cut-out in door/wall, towards the top of the cabinet</p>	 <p>Air inlet cut-out (required) Cut-out in cabinet floor</p>	Tap Positioning Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).  <p>35mm hole for HydroTap Tap</p>	Cutting detail Raised Font: <ul style="list-style-type: none"> 116mm diameter hole for bowl 164mm diameter hole for M6 stud 152mm diameter hole for tap  Font with 135mm Extension: <ul style="list-style-type: none"> 108mm diameter hole for bowl 164mm diameter hole for M6 stud 152mm diameter hole for tap 
			

**HydroTap G5
C Home**

shown with "Classic Plus" Tap

SCALE 1:5
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.