



# HYDROTAP G5 B ARC PLUS BRUSHED ROSE GOLD



**BOILING**

**FILTERED**

## Order Code H5L786Z05AU

Zip HydroTap Design Range Boiling, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 3 energy saving modes including ON/OFF timers and 2 hour sleep mode, antimicrobial protection impregnated into key water paths for enhanced hygiene, and 0.2 micron water filtration.



Manufacturing Code H5L786Z05AU

Capacity Residential

**Tap** Zip HydroTap Design Range ARC Plus Tap (Brushed Rose Gold)

**Water Pressure** Min 170kPa - Max 700kPa

**Water Connection** 1/2" BSP (G1/2)

**Water Supply Requirements** Cold

**Water Valves** Integrated 500kPa Pressure limiting valve and Dual Check Valve

**Power Rating** 1.35kW 220-240V 50Hz

**Power Supply** 1 x 10 Amp socket outlet

**Dimensions** W280mm x D313mm x H333mm

**Product Approvals** WaterMark, RCM

**Warranty** 5 years (appliance warranty 36 months plus additional 24 months tank warranty)

# Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.
3. Zip Micro is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com/book-service-visit](http://www.zipwater.com/book-service-visit)

## Installation Detail

BKL2 HydroTap G5 v1.10.07.04 B, BA

**Ventilation requirements** Contact your local service provider if ventilation is not suitable

**Clearance envelope**  
Position the Tap and the Command Centre as close together as possible.

200  
333  
50  
50  
Command Centre width

**HydroTap Tap options**

**HydroTap Arc Plus Tap**

**HydroTap Cube Plus Tap**

**Standalone Font with Arc Plus Tap**

**Cutting detail**  
for HydroTap Arc/Cube

3-off,  $\varnothing 10$  holes @ 155mm PCD, equispaced  
 $\varnothing 140$  hole for bowl  
 $\varnothing 176$  outline of Font  
 $\varnothing 35$  hole for tap

**Tap Positioning**  
Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount on a Font (available as an accessory).

4mm buffer pad air space

$\varnothing 35$ mm hole for HydroTap Plus Tap

HydroTap Arc Plus

Clearance Envelope

200 min.  
333

50 min. 280 50 min.

Mains cold water isolation valve (not supplied)

Air inlet grille

IEC Flex & Plug 230-240V, 50Hz power outlet

313

**HydroTap G5**  
B Home, B60, B100  
BA Home, BA60, BA100  
shown with HydroTap Arc Plus

SCALE 1:5  
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.