

60cm T Shape Rangehood

PRODUCT CODE: **EMT60CS**



FEATURES:

- + Stainless steel + black glass panel
- + Button control
- + 3 speed motor
- + 2 x 1.5W LED lights (Round)
- + Washable Aluminum grease filter
- + Max air extraction capacity 900m³/h
- + Air outlet 150mm

3 SPEED MOTOR

This rangehood provides the option of 3 different speed levels ensuring you have the option to use your rangehood at a low, medium or high level of operation.

HIGH EXTRACTION CAPACITY

The extraction capacity of 900m³/hr provides strength and power through the use of twin motors.

DISHWASHER SAFE CASSETTE FILTERS

Easy clean, stainless steel cassette filters, are designed to capture all steam and moisture, whilst removing exhaust and odours from the kitchen. Perfect for use over fast heat up cooktops, like induction.

Electrical Requirements

Rangehood is supplied with 10amp cord & plug.

Decibel Rating

66 dBA

Available Ventilation Kits

RHKE65EU	Wall – Eave vent kit
RHKMR65EU	Universal metal roof kit (includes flashing)
RHKTR65EU	Universal tile roof kit (includes flashing)

Rangehood Extensions

EMEXT (1 metre Extension)

Carbon Filter

CFMEM (requires 2)

Barcode

9347726027364



eurocooking



Warranty

HELPFUL TIPS

- + Leave your rangehood on for 15 minutes after the cooking of the food to remove all odors, steam etc.
- + The dishwasher-safe cassette filters need to be cleaned after approximately 2 months of standard operation
- + It is recommended that the rangehood be installed between 650mm and 750mm above the cooktop
- + It is also recommended that fumes from the rangehood be ducted out into the atmosphere.
- + Turn off the rangehood before attempting to clean

INSTALLATION

Installation is recommended by a qualified installer, please refer to the product manual for full installation instructions.

FILTER CLEANING INFORMATION

Cassette mesh filter: Requires cleaning monthly. This will ensure no interruptions with airflow operation.

