

Data Sheet: SHC



- > SHC 10 AU
-) SHC 15 AU





MAINS PRESSURE COMPACT STORAGE WATER HEATER


Made in Germany the SHC 10 AU and SHC 15 AU under bench mains pressure water heaters deliver hot water quickly to multiple sinks or basins. These point of use water heaters eliminate long runs of pipework for isolated sinks and basins and can greatly reduce the waiting time for hot water to arrive at the outlet. Installed directly underneath the basin or sink these water heaters are compact in design to take up less space in the cupboard.

		PLUS	
Model		SHC 10 AU	SHC 15 AU
		235002	235001
Tank capacity	L	10	15
Rated output (240 V)	kW	1.6	1.6
Rated current (240 V)	Α	6.8	6.8
Connection		1/N/PE	1/N/PE
Fuse protection	Α	10	10
Electrical installation		As per AS/NZS3000	
Installation requirements		AS/NZS3500.4.2 & local requirements	
Temperature settings	°C	60	60
Mixed water volume at 40 °C	L	15.3	23
Water connection		G 1/2 A	G 1/2 A
Max. permissible pressure	kPa	700	700
Supplied PTR valve	kPa	700	700
IP rating		IP24 D	IP24 D
Height (incl. PTR valve)	mm	498	523
Width	mm	280	320
Depth	mm	270	318
Weight (filled with water)	kg	17.2	24.0
Colour		White	White
Approvals		WaterMark Lic No. WMKA00301. AS3498	

The SHC compact storage water heater must be fitted with a safe tray and drain. Installation must be in accordance with AS/NZS3500.4.2 and local requirements.



SHC AU



	SHC 10	SHC 15
Height [A]	498	523
Width [B]	280	320
Depth [C]	270	318
Inlet Top Clearance [D]	26.5	23
Bracket - Height [E]	320	342
Bracket - Hole Spacing [F]	140	200

SHC Dimensions

