



# HYDROTAP G5 BCS CLASSIC PLUS BRUSHED NICKEL



**BOILING**



**CHILLED**



**SPARKLING**

**FILTERED**

## Order Code H55783Z11AU

Zip HydroTap Classic Plus Boiling, Chilled, Sparkling, Filtered water features simple, intuitive controls including continuous flow to fill bottles, Boiling water safety lock, and SteriTouch® antimicrobial protection impregnated within the new Classic Plus touch-pad for enhanced hygiene. The water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and 2 disposable CO2 cylinders.



Manufacturing Code H55783Z11AU

Capacity Residential

**Tap** Zip HydroTap CLASSIC PLUS Tap (Brushed Nickel)

**Water Pressure** Min 250kPa - Max 700kPa

**Water Connection** 1/2" BSP (G1/2)

**Water Supply Requirements** Cold

**Water Valves** Integrated 500kPa Pressure limiting valve and Dual Check Valve

**Power Rating** 1.53kW 220-240V 50Hz

**Power Supply** 1 x 10 Amp socket outlet

**Dimensions** W339mm x D460mm x H333mm

**Product Approvals** WaterMark, RCM, ARC

**Warranty** 5 years (appliance warranty 36 months plus additional 24 months tank warranty)

## Installation Requirements

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com](http://www.zipwater.com)'

## Installation Detail

BKL2 HydroTap G5 v1.00 02.21 BCS BCS20

<p><b>Ventilation requirements</b> Contact your local service provider if ventilation is not suitable</p> <p><b>Clearance envelope</b> Position the Tap and the Command Centre as close together as possible.</p>		<p><b>HydroTap Tap options</b></p> <p>Classic Plus Elite Plus</p>		<p><b>Font options</b></p> <p><b>Raised Font with 135mm Extension</b></p> <p><b>Font with 135mm Extension</b></p>	
<p><b>Tap Positioning</b> Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).</p> <p>35mm hole for HydroTap Tap</p>		<p><b>Cutting detail</b></p> <p>35mm hole for tap</p>		<p><b>Cutting detail</b></p> <p>35mm hole for tap</p>	
<p><b>Air outlet louvre (if required)</b> Cut-out in door/wall, towards the top of the cabinet</p> <p><b>Air inlet cut-out (required)</b> Cut-out in cabinet floor</p>		<p><b>4mm buffer pad air space</b></p>			
<p><b>Classic Plus Tap</b></p>				<p><b>Elite Plus Tap</b></p>	
<p><b>Clearance Envelope</b></p>		<p><b>Clearance Envelope</b></p>			
<p><b>Mains cold water isolation valve (not supplied)</b></p> <p><b>Air inlet grille</b></p> <p><b>IEC Flex &amp; Plug 230-240V, 50Hz power outlet</b></p> <p><b>CO<sub>2</sub> gas cylinder</b></p>		<p><b>460</b></p>			

SCALE 1:5  
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

**HydroTap G5  
BCS Home**

shown with "Classic Plus" Tap

