

**ITEM / SKU**

OCVB400B.....	4 Rolls Per Box, 400ft <sup>2</sup> (37.2m <sup>2</sup> )
OCVB7200P.....	72 Rolls Per Palletized Box, 7,200ft <sup>2</sup> (668.9m <sup>2</sup> )

**PRODUCT DIMENSIONS**

Roll Size .....	3' x 33'4" Roll, 100ft <sup>2</sup> (0.9m x 10.2m Roll, 9.3m <sup>2</sup> )
Roll Weight.....	13lbs (5.9kg)
4 Roll Box Dimensions .....	37.5"H x 12"W x 12"L (1m x 0.3m x 0.3m)
4 Roll Box Weight .....	53lbs (24kg)
72 Roll Palletized Box Dimensions .....	49"H x 48"W x 40"L (1.2m x 122m x 1m)
72 Roll Palletized Box Weight .....	980lbs (444.5kg)

**PRODUCT SPECIFICATIONS\***

Material Composition .....	Frothed Polyurethane Foam with Polyethylene Vapor Barrier
Thickness (ASTM D3574) .....	0.055" (1.4mm)
Density (ASTM D3574) .....	25lbs/ft <sup>3</sup> (400.5kg/m <sup>3</sup> )
Compression Set (ASTM D3574) .....	5% max
Tensile Strength (ASTM D3574) .....	100lbs/ft <sup>2</sup> (488.2kg/m <sup>2</sup> )
Indentation Load Deflection - 25% (ASTM D3574) .....	32lbs/ft <sup>2</sup> (156.2kg/m <sup>2</sup> )
Indentation Load Deflection - 65% (ASTM D3574) .....	200+lbs/ft <sup>2</sup> (976.5+kg/m <sup>2</sup> )
NBS Smoke Density (ASTM E662) .....	<100 max
Flammability Test (DOC FF 1-70).....	Pass
Thermal Transmission R-Value (ASTM C518) .....	0.08 °F ft <sup>2</sup> h/Btu (Excellent for Radiant Heated Floors)
Water Vapor Transmission (ASTM E96) .....	0.46 grains/h•ft <sup>2</sup>
Antimicrobial Protection .....	Ultra-Fresh® Antimicrobial Protection
Indoor Air Quality.....	UL GREENGUARD® GOLD Certified for Low Chemical Emissions - UL2818
Installation Method .....	Approved for Floating and Nail-Down Installation
Warranty .....	Warranted for Equal Term to that of the Primary Floor Covering
Moisture & Vapor Warranty (ASTM F1869).....	Warranted up to 10lbs / 1,000ft <sup>2</sup> / 24hrs of Vapor Emissions

\*Specifications are Subject to ±10% Manufacturing Tolerance.

**SOUND RATING\***

Laminate & Wood Floors (ASTM E492).....	71 IIC
Laminate & Wood Floors (ASTM E413).....	67 STC
Luxury Vinyl Tile (LVT) (ASTM E492) .....	73 IIC
Luxury Vinyl Tile (LVT) (ASTM E413) .....	67 STC

\*The Results of the Impact Insulation Class (IIC) and Sound Transmission Class (STC) are Influenced by the Complete Floor-Ceiling Construction.

**SUSTAINABILITY & RECYCLABILITY**

Renewable & Natural Content .....	>50% (Made in Part with Soybean Oil and Other Natural Non-Petrochemical Resources)
Recyclability .....	100% Post-Consumer Recyclable
LEED Credit IEQ 4.3 .....	Low-Emitting Materials-Flooring Systems
LEED Credit MR 6.0 .....	Rapidly Renewable Materials
LEED Credit MR 5.1 .....	10% Extracted, Processed & Manufactured Regionally
LEED Credit MR 5.2 .....	20% Extracted, Processed & Manufactured Regionally

