



# **Product Specifications**

VV704 Style Number

Construction Waterproof Foamed Core

**Edge Profile** Pressed Bevel **Nominal Dimensions** 7" wide, 48" long

	US Units	Metric Units
Actual Product Width	7.05"	17.91 cm
Actual Product Length	48.03"	122 cm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Overall Product Thickness	0.295"	7.5 mm
Core Thickness	0.197"	5 mm
Attached Underlayment	Attached Cork	
Attached Underlayment	0.039"	1 mm
Thickness		
Finish	UV Acrylic	
Installation Methods	Floating or Direct Glue	
Profile	Angle/Tap	
Country of Origin	Imported	



## **Packaging**

Area per Box 18.8 sq ft 1.75 sq m Pieces per Box 8 pcs Weight per Box 30.42 lbs 13.79 kg **Boxes per Pallet** 70 boxes



### Warranties

**USF** Lifetime Limited

USF 10 Year Medium Commercial

### Certifications

GreenGuard (Certification, Gold, Private Label) Certified



## **Coordinating Trim**









T-Molding\*
TM7CT | 94"



Multi-Purpose Reducer\*

RD7CT | 94"



Quarter Round
QTRCT | 94"



Flush Stairnose
FS7HU | 94"
\*Packaged with molding track