

Product Specifications

Style Number	VV465	
Construction	Solid Polymer Core	
Edge Profile	Micro Bevel	
Nominal Dimensions	7" wide, 48" long	
	US Units	Metric Units
Actual Product Width	7.13"	18 cm
Actual Product Length	48.03"	122 cm
Wear Layer Thickness	12 mil (0.012")	0.3 mm
Overall Product Thickness	0.173"	4.4 mm
Attached Underlayment	Attached Cork	
Attached Underlayment Thickness	0.039"	1 mm
Finish	UV Acrylic	
Installation Methods	Floating or Direct Glue	
Profile	Angle/Tap	
Country of Origin	Imported	

Packaging


Area per Box	28.52 sq ft	3 sq m
Pieces per Box	12 pcs	
Weight per Box	41.89 lbs	19 kg
Boxes per Pallet	45 boxes	



2060 Whirlpool Oak

Colors





2082 Solstice Cherry



2083 Centaurus Oak

Performance

Static Load (ASTM F970)	Passes
Residual Indentation (ASTM F1914)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Smoke Density (ASTM E662)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant


Warranties

30 Years
7 Year Light Commercial

Certifications

GreenGuard (Certification, Gold, Private Label) Certified

Coordinating Trim




Baby Threshold*

04Z02 | 94"



T-Molding*

04Z01 | 94"




Overlap Reducer*

04Z03 | 94"




Quarter Round

04Z00 | 94"



Overlap Stairnose*

04Z04 | 94"



Flush Stairnose

04Z05 | 94"

*Packaged with molding track