

Product Specifications

Style Number	VV662	
Construction	Waterproof Foamed Core	
Edge Profile	Enhanced Painted Bevel	
Nominal Dimensions	9" wide, lengths of 28", 55" and 82"	
	US Units	Metric Units
Actual Product Width	8.97"	23 cm
Actual Product Length	Multiple Lengths 27.55", 55.11" and 82.67"	Multiple Lengths 70 cm, 140 cm and 210 cm
Wear Layer Thickness	30 mil (0.03")	0.76 mm
Overall Product Thickness	0.59"	15 mm
Core Thickness	0.472"	12 mm
Attached Underlayment	Attached Cork	
Attached Underlayment Thickness	0.118"	3 mm
Installation Methods	Floating or Direct Glue	
Profile	Angle/Tap	
Country of Origin	Imported	
Packaging		
Area per Box	20.67 sq ft	2 sq m
Pieces per Box	18 pcs	
Weight per Box	63.14 lbs	28.63 kg
Boxes per Pallet	36 boxes	



3003 Grande Willis O

Colors



COREtec PlusGrande

Performance

Residual Indentation (ASTM F1914)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Smoke Density (ASTM E662)	Passes
Radiant Panel (ASTM E648)	Passes, Class I

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

USF Lifetime
 Resid Resil Ltd Wty Df Wr Wp Ptpresid Resil Ltd Wty Def Wr Wp Petp
 USF 10 Year Medium Commercial


Certifications

GreenGuard (Certification, Gold, Private Label) Certified


Coordinating Trim




Baby Threshold*
B15HC | 94"



T-Molding*
T15HC | 94"



Quarter Round
QTRCT | 94"



Flush Stairnose
F15HC | 94"

*Packaged with molding track

Stair Tread



Stair Tread
03Z70 | 48"

