# **Pro Series** High Definition (HD) Digital Video Scopes

### **Video Monitor:**

- Monitor: 3.5" full view IPS LCD
- Resolution: 1280 x 720
- Photos and videos
- Date & Time stamp
- Digital Zoovm: 1.4x / 1.6x / 2x
- Upside down image flip
- Brightness adjustment
- Battery: 1500mAh lithium polymer
- Supports 13 languages
- Solid rubber boot protector for shock resistance
- Dimensions: 18.5cm x 10.0cm x 3.2cm (7.3" x 3.9" x 1.3")
- Weight: 252g (8.9oz)

#### **Probes:**

• IP67 rated dust and fluid

 Resistant to all fuels, water, coolants, oils, brake fluid and transmission fluid

Temperature range: 0 - 55°C (32 - 131°F) The world's first and smallest models of Digital Video Scopes with full High-Definition resolution
















Engine

**Under Car** 

A/C

Exhaust

Brakes

Body



## **Video Scope Kits**

### **DVSK-45DC**

## **HD Digital Video Scope Kit w/ 4.5mm Dual Camera Probe**

The most versatile small diameter high-definition digital video scope kit. Comes with the 4.5mm diameter Dual Camera imaging probe, allowing the user to view forward and side views with just a flick of a button, without the need for a mirror or multiple probes to do the same job.



#### The DVSK-45DC kit contains:

- Main monitor device
- 4.5mm Dual Camera probe
- 8G SD mini card
- USB cable for charging
- User manual
- In a zippered carrying case (7.9" x 4.7" x 2.8" / 1.1 lbs.)

## **DVSK-60ART**HD Digital Video Scope Kit w/ 6.0mm Articulation Probe

The most in demand video scope kit. The 6.0mm diameter Articulation imaging probe lets the user look back up to 180°. Great for any engine work.



#### The DVSK-60ART kit contains:

- Main monitor device
- 6.0mm Articulation probe
- 8G SD mini card
- USB cable for charging
- User manual
- In a cardboard box with foam insert carrying case (15.8" x 7.9" x 3.2" / 1.98 lbs.)

## **Imaging Probes**

### **DP39**

## 3.9mm HD Digital Imaging Probe (Front View)

- Smallest diameter probe
- Designed for wok on diesel TDI engines, diesel injection ports, glow plug ports, door & window frame and other narrow access applications



### DP45C

## **4.5mm HD Digital Dual Camera Imaging Probe**

- Front and side view cameras combined in one imaging probe provides more than a 110° field of view
- Switch easily from side to front views with a single button



# DP60ART 6.0mm HD Digital Articulation Imaging Probe

- With an articulation field of view of 180°, no need for a mirror adaptor!
- Two-way articulation wheel control for easy manipulation



## **Technical Specifications**

	DP39	DP45DC	DP60ART
Description	3.9mm HD Digital Imaging Probe (Front View)	4.5mm HD Digital Dual Camera Imaging Probe	6.0mm HD Digital Articulation Imaging Probe
Diameter	3.9mm	4.5mm	6.0mm
Length	1m	1m	1m
Waterproof	IP67	IP67	IP67
Digital Resolution	1280 x 720 pixels	1280 x 720 pixels	1280 x 720 pixels
Field of View (FOV)	80 degrees	60 degrees	60 degrees
Depth of Field (DOF)	3-8cm	3-8cm	2-5cm
LED lights	6	front view/6, side view/4	6

## Replacement probes available for the Analog Kits ANSED/VS-49, ANSED/VS-ARTONE and ANSED/VS-55:

39FV
3.9mm Front View Probe
39SV
49SW
4.9mm Dual Camera Probe
5.5mm Standard Camera Probe

**ARTONE** 6 mm Articulation Probe

For more information:



ANSED Diagnostic Solutions LLC 1528 Walnut Street Suite 1600 Philadelphia, PA 19102 888.685.7287

sales@anseddiagnostics.com www.anseddiagnostics.com