



Product name


Universal 2-jaw puller with adjustable reach

For removing bearings, gears, discs, etc.

Art. No. 20-40-AV

Series 20-AV/20-5

EAN 4021176973222



	Technical attribute	Metric	Imperial
	Spread	80 - 650 mm	3 3/16 - 25 5/8 inch
	Depth	300 - 500 mm	11 7/8 - 19 3/4 inch
	Spread used internal	200 - 710 mm	7 7/8 - 28 13/32 inch
	Hexagon drive (male)	36 mm	
max.	Maximum load	12 t	1 US t
	Maximum torque	400 Nm	295 ft lb
	Weight	20 kg	
	Space below	25 mm	1 inch
	Space next to it	85 mm	3 3/8 inch
	Number of jaws	2	2



Technologies



SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



Spare part

Art. No.	Product name
633500	Mechanical pressure spindle.
4-SP-P	2 pulling jaws with adjustable length (pair)
20-40-T	2-jaw cross bar

Accessories

Art. No.	Product name
8-1-B	Long hydraulic spindle
9-1	Auxiliary hydraulic ram
9-2	Auxiliary hydraulic ram
9-3	Auxiliary hydraulic ram
11-520	Cross-beam for puller 11-1
3-200-P	2 pulling jaws (pair)
3-300-P	2 extended jaws (pair)
3-400-P	2 extended jaws (pair)
3-500-P	2 extended jaws (pair)
3-200-E	Jaws (individual)
4-SP-E	Jaws (individual)
3-250-P	2 pulling jaws (pair)



Can be used alternatively with

Art. No.	Product name
9-2	Auxiliary hydraulic ram
9-3	Auxiliary hydraulic ram
3-202-P	2 quick adjusting jaws (pair)
3-302-P	2 quick adjusting jaws (pair)
3-402-P	2 quick adjusting jaws (pair)
3-502-P	2 quick adjusting jaws (pair)