

PROJECT NAME	
ORDERING #	TYPE



DETAILS

Streamline your fluorescent retrofit. Not only do our Type B Ballast Bypass direct wire 4ft LED tubes remove the need to install entirely new fixtures during your LED conversion, their double-ended power makes it so that even the tube installation will be as painless as possible. These tubes also offer a 240° beam angle for excellent coverage of any area you're looking to light. LED tubes powered on both sides fit both shunted and non-shunted ends of most fluorescent lampholders, or tombstones, removing a central step of the retrofit process and saving you time with each and every install.



SPECIFICATIONS

Input Power	14W
Input Voltage	120~277VAC
Light Output	1,800 lm
System Efficacy	129 lm/w
CCT	4000K, 5000K
CRI	>80
Average Lamp Life	50,000 hours
Base Type	Bi-Pin
Cover	Frosted
Ballast Compatibility	Compatible with all fluorescent fixtures—Bypass the ballast before installing tube
Beam Angle	240°
Tube Length	4'
Certification	DLC 5.1 Pending, UL
Warranty	5 years

ORDERING

Example: **4RLDET8014UN40F**

SKU Root	Wattage / Lumens		CCT	Finish
4RLDET8	014 - 14W, 1,800 lm	UN	40 - 4000K 50 - 5000K	F - Frosted

ACCESSORIES

Item Type	SKU	Description	Image
Holder	ACCXG13UNSHUNTD	G13 Nonshunted Lamp Holder for 4' Bi-Pin Tube Lights	