

Project Name: _____

Ordering #: _____ Type: _____



5 YEAR WARRANTY

OVERVIEW	
Tube Length	4'
Wattage (W)	14W
Lumen Package (lm)	1,800 lm regular 1,050/500 lm emergency
Color Temperature (CCT)	5000K
Efficacy (lm/W)	129 lm/W



ORDERING GUIDE


Example: **4EMT8M14W50F**

SKU Root	Wattage / Lumens	CCT	Finish
4EMT8M	14W - 14W, Up to 1,800 lm	50 - 5000K	F - Frosted

SPECIFICATIONS

Tube Length	4'
Wattage & Lumens	14W, 1,800 lumens regular / 1,050/500 lumens emergency
Efficacy	129 lm/W
CCT	5000K
CRI (Ra)	83
Input Voltage	120-277VAC
Average Lifetime	50,000 hours
Cover	Frosted
Base Type	Bi-Pin
Installation	Ballast bypass requiring non-shunted tombstones on both sides; Wall switch side is Type B single-end power while the emergency end of the tube requires constant power
Emergency Battery	24 hour charge time, 90 minute operating time
Housing Material	Aluminum & Polycarbonate
Certifications	ETL
Warranty	5 Years

PRODUCT DIMENSIONS



Dimension	Minimum	Typical	Maximum
A	47.13 inch	47.16 inch	47.22 inch
B	47.4 inch	/	47.5 inch
C	/	/	47.78 inch