

Project Name: \_\_\_\_\_

Ordering #: \_\_\_\_\_ Type: \_\_\_\_\_



**5** YEAR WARRANTY



### OVERVIEW

<b>Tube Length</b>	4'
<b>Wattage (W)</b>	18W, 24W
<b>Lumen Package (lm)</b>	Up to 4,320 lm
<b>Color Temperature (CCT)</b>	5000K
<b>Efficacy (lm/W)</b>	Up to 183 lm/W

### ORDERING GUIDE

Example: **4HLT8M18W50C**

SKU Root	Wattage / Lumens	CCT	Finish
<b>4HLT8M</b>	<b>18W</b> - 18W, 3,300 lumens	<b>50</b> - 5000K	<b>C</b> - Clear <b>F</b> - Frosted
<b>4UHLT8M</b>	<b>24W</b> - 24W, 4,320 lumens		

### SPECIFICATIONS

<b>Tube Length</b>	4'
<b>Wattage &amp; Lumens</b>	18W, 3,300 lumens 24W, 4,320 lumens
<b>Efficacy</b>	18W: 183 lm/W 24W: 180 lm/W
<b>CCT</b>	5000K
<b>CRI (Ra)</b>	>83
<b>Input Voltage</b>	120-277VAC
<b>Average Lifetime</b>	50,000 hours
<b>Base Type</b>	G13 (Medium Bi-Pin)
<b>Installation</b>	Type B ballast bypass with single-ended or double-ended power
<b>Lens</b>	Clear or Frosted
<b>Certifications</b>	ETL
<b>Warranty</b>	5 Years