

Project Name: _____

Ordering #: _____ Type: _____



OVERVIEW	
Wattage (W)	38W (100%, 80%, 60%, or 40% power) 100W (100%, 80%, 60%, or 40% power) 135W
Lumen Package (lm)	Up to 20,000 lm
Color Temperature (CCT)	38W, 100W: 3000K/4000K/5000K Selectable 135W: 4000K or 5000K
Efficacy (lm/W)	Up to 158 lm/W



SPECIFICATIONS

Wattage & Lumens	38W, Up to 6,000 lumens 100W, Up to 15,500 lumens 135W, 20,000 lumens
Efficacy	Up to 158 lm/W
CCT	38W: 3000K/4000K/5000K Selectable 100W: 3000K/4000K/5000K Selectable 135W: 4000K or 5000K
CRI (Ra)	70
Controls	38W & 100W: CCT & Power Selectable
Input Voltage	120-277VAC or 347-380VAC
Average Lifetime	50,000 hours
Certifications	DLC, UL
Warranty	5 Years

ORDERING GUIDE

Example: **WPFCM15D038WSCS**

SKU Root	Wattage / Lumens	Power	CCT
WPFCM15D	038 - 38W, Up to 6,000 lumens 100 - 100W, Up to 15,500 lumens	WS - Power Selectable (100%, 80%, 60%, or 40%)	CS - 3000K/4000K/5000K Selectable
	135 - 135W, 20,000 lumens	W - Fixed	40 - 4000K 50 - 5000K