

PROJECT NAME	
ORDERING #	TYPE

5 YEAR WARRANTY

DETAILS

Meets standards for use in the following harsh or hazardous environments:
 Class I, Division 2, Groups A, B, C, D • Class II, Division 1, Groups E, F, G
 Class II, Division 2, Groups F, G • Class III • Wet Locations

SPECIFICATIONS

Input Power	240W, 200W, 180W, 150W, 100W, 75W, 30W
Input Voltage	100-277VAC
Light Output	240W - 33,600 lumens 200W - 28,000 lumens 180W - 25,200 lumens 150W - 21,000 lumens 100W - 14,000 lumens 75W - 10,500 lumens 30W - 4,200 lumens
Efficiency	140 lm/W
CCT	5000K
CRI	>70
Beam Angle	Type III
Working Environment	Harsh and hazardous locations, indoor or outdoor
Enclosure Rating	IP66, IK08
Average Lamp Life	50,000 hours
Certifications	IECEX, ATEX
Warranty	5 Years



100W, 75W, 30W



240W, 200W, 180W, 150W

ORDERING

Example: **EXP5HA030WUL50CM**

SKU Root	Wattage / Lumens	Voltage	CCT	Mounting Option
EXP5HA	030W - 30W, 4,200 lumens 075W - 75W, 10,500 lumens 100W - 100W, 14,000 lumens 150W - 150W, 21,000 lumens 180W - 180W, 25,200 lumens 200W - 200W, 28,000 lumens 240W - 240W, 33,600 lumens	UL - 100-277VAC	50 - 5000K	CM - Ceiling Mount PM - Pendant Mount WB - Wall Bracket SM - 25° Stanchion Mount SMV - 90° Stanchion Mount TM - Trunnion Mount