

Project Name: \_\_\_\_\_

Ordering #: \_\_\_\_\_ Type: \_\_\_\_\_



## OVERVIEW

<b>Wattage (W)</b>	750W
<b>Lumen Package (lm)</b>	105,000 lm
<b>Color Temperature (CCT)</b>	5000K
<b>Efficacy (lm/W)</b>	140 lm/W

## SPECIFICATIONS

<b>Wattage &amp; Lumens</b>	750W, 105,000 lumens
<b>Efficacy</b>	140 lm/W
<b>CCT</b>	5000K
<b>CRI (Ra)</b>	>70
<b>Input Voltage</b>	100-277VAC
<b>Average Lifetime</b>	50,000 hours
<b>Beam Angle</b>	40°
<b>Recommended Installation Height</b>	>50 feet
<b>Mounting</b>	Bracket
<b>Enclosure Rating</b>	IP65
<b>Certifications</b>	DLC, UL
<b>Warranty</b>	5 Years



## ORDERING GUIDE

Example: **LGBSFL02750W50ULBLFM**

SKU Root	Wattage / Lumens	CCT	Voltage	Housing Color	Mounting
<b>LGBSFL02</b>	<b>750W</b> - 750W, 105,000 lumens	<b>50</b> - 5000K	<b>UL</b> - 100-277VAC	<b>BL</b> - Black	<b>FM</b> - Bracket Flood Mount

## PRODUCT DIMENSIONS

