

PROJECT NAME	
ORDERING #	TYPE

5 YEAR WARRANTY

DETAILS

Engineered with energy efficiency and longevity in mind, this high mast lighting solution is perfect for highways, ports, airports, industrial zones, stadiums, and more.

SPECIFICATIONS

Input Power	400W, 480W, 600W, 800W, 960W, 1200W
Input Voltage	120-277VAC or 277-480VAC
Light Output	400W: 60,000 lumens 480W: 72,000 lumens 600W: 90,000 lumens 800W: 120,000 lumens 960W: 144,000 lumens 1200W: 180,000 lumens
System Efficacy	150 lm/W
CCT	5700K (Contact us for 3000K and 4000K)
CRI	>70 (Contact us for CRI >80 and >90)
Average Lamp Life	50,000 hours
Enclosure Rating	IP66, IK08
Dimensions	400W: Light Module: 17.40" W x 6.65" H x 4.29" D / With bracket: 18.86" W x 9.84" x 7.28" D 480W: Light Module: 17.40" W x 7.95" H x 4.29" D / With bracket: 18.86" W x 10.47" x 7.28" D 600W: Light Module: 17.40" W x 9.25" H x 4.29" D / With bracket: 18.86" W x 11.14" x 7.28" D 800W: Light Module: 17.40" W x 14.09" H x 4.29" D / With bracket: 20.08" W x 16.89" x 9.13" D 960W: Light Module: 17.40" W x 16.69" H x 4.29" D / With bracket: 20.08" W x 20.75" x 11.38" D 1200W: Light Module: 17.40" W x 19.29" H x 4.29" D / With bracket: 20.08" W x 22.05" x 11.38" D
Warranty	5 years





ORDERING

Example: **SPTX400ED57K27V**

SKU Root	Beam Angle	Wattage/Lumens	Driver	CCT	Voltage	Options
SPT	30 - 30°	400 - 400W, 60,000 lumens	ED - External Driver	57K - 5700K	27V - 120-277V 48V - 277-480V	BLANK - None
	T3 - Type III	480 - 480W, 72,000 lumens				
	45 - 45°	600 - 600W, 90,000 lumens				
	60 - 60°	800 - 800W, 120,000 lumens				
		960 - 960W, 144,000 lumens				
		1200 - 1200W, 180,000 lumens				

ACCESSORIES

Item Type	SKU	Description	Image
Adjustment Device	ACCXSPTAIMDEVICE	Luminaire Aiming Device	
Visor	ACCXSPTVISOR	Visor	
Converter	ACCXSPTLIFUDDALI	Lifud DALI Converter	