

Project Name: \_\_\_\_\_

Ordering #: \_\_\_\_\_ Type: \_\_\_\_\_



OVERVIEW	
<b>Wattage (W)</b>	100W, 150W, 200W, 300W
<b>Lumen Package (lm)</b>	Up to 42,000 lm
<b>Color Temperature (CCT)</b>	5000K
<b>Efficacy (lm/W)</b>	140 lm/W



## SPECIFICATIONS

<b>Wattage &amp; Lumens</b>	100W, 14,000 lumens 150W, 21,000 lumens 200W, 28,000 lumens 300W, 42,000 lumens
<b>Efficacy</b>	140 lm/W
<b>CCT</b>	5000K
<b>CRI (Ra)</b>	>70
<b>Controls</b>	0-10V Dimming
<b>Input Voltage</b>	100-277VAC
<b>Average Lifetime</b>	50,000 hours
<b>Beam Angle</b>	30° x 60°
<b>IP Rating</b>	IP66
<b>Dimensions</b>	100W: 15.35" x 13.07" x 3.03" 150W: 17.05" x 12.91" x 3.03" 200W: 18.54" x 15.55" x 3.43" 300W: 21.18" x 18.31" x 3.78"
<b>Certifications</b>	DLC, ETL
<b>Warranty</b>	5 Years

## ORDERING GUIDE

Example: **FLOOD70HM100DD50**

SKU Root	CRI	Series	Wattage / Lumens	Controls	CCT
<b>FLOOD</b>	<b>70 - 70</b>	<b>HM</b>	<b>100</b> - 100W, 14,000 lumens <b>150</b> - 150W, 21,000 lumens <b>200</b> - 200W, 28,000 lumens <b>300</b> - 300W, 42,000 lumens	<b>DD</b> - 0-10V Dimming	<b>50</b> - 5000K

**ACCESSORIES**

SKU	Description	Image
FL08XPOLEMNT60MM	60MM Diameter Pole Mount for Flood Lights	