

Project Name: \_\_\_\_\_

Ordering #: \_\_\_\_\_ Type: \_\_\_\_\_



### OVERVIEW

<b>Wattage (W)</b>	60W/46W/36W/22W Selectable
<b>Lumen Package (lm)</b>	Up to 7,700 lumens
<b>Color Temperature (CCT)</b>	4000K/5000K Selectable
<b>Efficacy (lm/W)</b>	Up to 163 lm/W



### ORDERING GUIDE

Example: **CANOPYM3D060WSCS**

SKU Root	Wattage / Lumens	CCT
CANOPYM3D	<b>060WS</b> - 60W/46W/36W/22W Selectable, Up to 7,700 lumens	<b>CS</b> - 4000K/5000K Selectable

### SPECIFICATIONS

<b>Wattage &amp; Lumens</b>	60W/46W/36W/22W Selectable, Up to 7,700 lumens
<b>Efficacy</b>	Up to 163 lm/W
<b>CCT</b>	4000K/5000K Selectable
<b>CRI (Ra)</b>	70
<b>Input Voltage</b>	120-277VAC
<b>Average Lifetime</b>	50,000 hours
<b>Beam Angle</b>	Parking Garage Photometry
<b>Lens Cover</b>	Clear
<b>Mounting</b>	J-Box or Pendant Mount
<b>Housing Material</b>	One-piece sealed die-cast housing with polycarbonate lens
<b>Housing Color</b>	White
<b>Dimensions</b>	12" diameter x 3.32" high
<b>Certification</b>	DLC, UL
<b>Warranty</b>	5 Years