

Project Name: _____

Ordering #: _____ Type: _____



OVERVIEW

Wattage (W)	100W/80W/60W/40W Selectable 150W/120W/90W/60W Selectable
Lumen Package (lm)	Up to 23,000 lumens
Color Temperature (CCT)	5000K
Efficacy (lm/W)	Up to 170 lm/W



ORDERING GUIDE

Example: **CANOPYMID100WS50**

SKU Root	Wattage / Lumens	CCT
CANOPYMID	100WS - 100W/80W/60W/40W Selectable, Up to 15,000 lm	50 - 5000K
	150WS - 150W/120W/90W/60W Selectable, Up to 23,000 lm	

SPECIFICATIONS

Wattage & Lumens	100W/80W/60W/40W Selectable, Up to 15,000 lumens 150W/120W/90W/60W Selectable, Up to 23,000 lumens
Efficacy	Up to 170 lm/W
CCT	5000K
CRI (Ra)	>70
Controls	Power Selectable
Input Voltage	120-277VAC
Average Lifetime	50,000 hours
Lens Cover	Clear
Beam Angle	General Distribution
Housing Material	Die cast aluminum with fade-resistant powder coat finish
Housing Color	White
Dimensions	15.75" x 15.75" x 8.78"
Certifications	DLC, UL
Warranty	5 Years