

PROJECT NAME	
ORDERING #	TYPE



### DETAILS

Whether you need 4,200 lumens or 16,000, this highly adaptable parking garage light with built-in 1,350 lumen uplight will uplift any parking structure you install it in. This luminaire is both attractive and built tough, capable of withstanding dust, damp, water jets, impact, and both sweltering and freezing temperatures. Cut energy costs, increase safety, and elevate your garage, all at once.



### SPECIFICATIONS

<b>Input Power</b>	100W (100%, 75%, 50%, and 30% power settings)
<b>Input Voltage</b>	120-277VAC
<b>Light Output</b>	4,200 to 16,000 lumens, dependent on power and CCT settings, plus a 1,350 lumen uplight
<b>System Efficacy</b>	160 lm/W at 4000K, 150 lm/W at 5000K, 140 lm/W at 3000K
<b>CCT</b>	3000K/4000K/5000K Selectable
<b>CRI</b>	70
<b>Average Lamp Life</b>	50,000 hours
<b>Beam Angle</b>	Type V
<b>Dimming</b>	1-10V
<b>Installation</b>	Surface or Pendant (3/4" NPT) Mount
<b>Enclosure Rating</b>	IP65, IK08
<b>Temperature Rating</b>	-22°F - 122°F
<b>Housing Material</b>	Aluminum alloy with polycarbonate lens
<b>Housing Color</b>	White
<b>Dimensions</b>	12.7" diameter x 3.3" high
<b>Certification</b>	ETL
<b>Warranty</b>	5 years

### ORDERING

Example: **CANOPY02A100WSCS**

SKU Root	Wattage / Lumens	CCT
CANOPY02A	100WS - 100W/75W/50W/30W, Up to 16,000 lumens	CS - 3000K/4000K/5000K Selectable

### DIMENSIONS

