Selectable Semi-Cutoff LED Wall Pack

Project Name:		
Ordering #:	Ty	ype:

DI	LC
LIS'	TED





OVERVIEW		
Wattage (W)	65W Selectable (100%, 80%, 60%, or 40%)	
Lumen Package (lm)	Up to 8,300 lm	
Color Temperature (CCT)	3000K/4000K/5000K Selectable	
Efficacy (Im/W)	Up to 128 lm/W	



SPECIFICATIONS

Wattage & Lumens	65W, Up to 8,300 lumens
Efficacy	Up to 128 lm/W
сст	3000K/4000K/5000K Selectable
CRI (Ra)	70
Controls	1-10V Dimming CCT & Power Selectable
Input Voltage	120-277VAC
Average Lifetime	50,000 hours
Beam Angle	110°
Cover	Clear
Enclosure Rating	cUL Wet Location
Housing Color	Bronze
Dimensions	14.2" x 9.25" x 7.08"
Certifications	DLC, UL
Warranty	5 Years

ORDERING GUIDE

Example: WPCKSM8065UDCSN

SKU Root	Wattage / Lumens	Certifications	сст	
WPCKSM8	065 - 65W, Up to 8,300 lumens	UD - DLC, UL	CS - 3000K/4000K/5000K Selectable	N

ACCESSORIES

SKU	Description	Image
PHOTOCELLSENSWP	Photocell for Wall Packs	PROPOSALISTICS BEING COMMUNICATION FROM ACCIDENCE COMMUNICATION FROM ACCIDENCE COMMUNICATION ACCIDENCE