

Project Name: _____

Ordering #: _____ Type: _____



OVERVIEW	
Size	13", 15", 20"
Wattage (W)	16W, 22W, 26W
Lumen Package (lm)	Up to 2,080 lm
Color Temperature (CCT)	2700K/3000K/3500K/4000K/5000K Selectable
Efficacy (lm/W)	80 lm/W



ORDERING GUIDE

Example: **MMH13FM16WCSNK**


SKU Root	Size (Diameter)	Mounting	Wattage / Lumens	CCT	Finish
MMH	13 - 13"	FM - Flush Mount	16W - 16W, 1,280 lumens	CS - 2700K/3000K/3500K/4000K/5000K Selectable	NK - Brushed Nickel BK - Matte Black GD - Brushed Gold
	15 - 15"		22W - 22W, 1,760 lumens		
	20 - 20"		26W - 26W, 2,080 lumens		

PRODUCT DIMENSIONS

DIMENSIONS	16W (13")	22W (15")	26W (20")
Product Dimension	Φ12.99" x 2.56" / Φ330mm x 65mm	Φ15.35" x 2.56" / Φ390mm x 65mm	Φ19.29" x 2.56" / Φ490mm x 65mm

Front View

Side View



L1	φ 330mm / 12.99"	φ 390mm / 15.35"	φ 490mm / 19.29"
L2	65mm / 2.56"	65mm / 2.56"	65mm / 2.56"

SPECIFICATIONS

Size	13", 15", 20"
Wattage & Lumens	(13") 16W, 1,280 lumens (15") 22W, 1,760 lumens (20") 26W, 2,080 lumens
Efficacy	80 lm/W
CCT	2700K/3000K/3500K/4000K/5000K Selectable
CRI (Ra)	80
Controls	Compatible with Leviton DSL06, Leviton IPL06, or LUTRON DVCL-153P Dimming Controller CCT Selectable
Input Voltage	120VAC
Average Lifetime	50,000 hours
Beam Angle	120°
Mounting	Flush Mount
Lens	White Acrylic
Finish	Brushed Nickel, Matte Black, Brushed Gold
Certifications	ETL