

PROJECT NAME	
ORDERING #	TYPE



DETAILS

Incredible efficiency with a luminous efficacy of up to 176 lm/W. Flexible fixture comes with 4 lumen packages and 3 color temperatures, selectable during installation, that provide 12 possible configurations for the light.



SPECIFICATIONS

Input Power	41/63/85/110W selectable
Input Voltage	120-277 VAC
Light Output	Up to 7,200/10,500/13,600/16,500 lumens
Efficiency	Up to 176 lm/W
CCT	3000K/4000K/5000K selectable
CRI	>70
Average Lamp Life	50,000 hours
Lens Cover	Clear
Light Type	Wired fixture
Operating Temperature	-40°F to 104°F
Installation	J-box mount or 3/4" conduit mount; includes 1/2" knock-out holes on three sides
Housing Material	Die cast aluminum with fade-resistant powder coat finish
Housing Color	Dark bronze
Dimensions	11.52" x 11.52" x 3.8"
Certification	DLC, UL
Warranty	5 Years

ORDERING

Example: **CANOPYM7D110WSCS**

SKU Root	Wattage / Lumens	CCT
CANOPYM7D	110WS - 41/63/85/110W Selectable, Up to 16,500 lm	CS - 3000K/4000K/5000K Selectable