

PROJECT NAME	
ORDERING #	TYPE



DETAILS

Our Wattage & Color Selectable LED High Bay is designed with various beam angles, perfect for high-mounting applications, including: warehouses, industrial facilities, exhibition centers, shopping malls, gymnasiums, factories, airports, toll stations, and more.



SPECIFICATIONS







Input Power	100W, 120W, 150W, 200W
Input Voltage	100-277VAC, 50-60 Hz
Light Output	Up to 30,000 lumens
Efficiency	Up to 150 lm/W
CCT	4000K/5000K
CRI	80
Average Lamp Life	50,000 hours
Controls	Dimmable, PIR Sensor
Mounting	Loop Hanging, Ceiling Mounting
Enclosure Rating	IP65
Certifications	DLC, ETL
Warranty	5 years

ORDERING

Example: **HD120HB382002CCTULBL**

SKU Root	Wattage	CCT	Voltage	Fixture Color
HD120HB38	200 - 100W/120W/150W/200W Selectable	2CCT - 4000K, 5000K Selectable	UL - 100-277 VAC	BL - Black

ACCESSORIES

Item Type	SKU	Description	Image
Sensor	ACCXHB38SENSOR	Plug-and-play Bi-level PIR Sensor	
Remote	ACCXHB38REMOTE	Remote Controller for PIR Sensor	
Lens	ACCXHB3890DEGLENS	90° Optic Lens	
Lens	ACCXHB3860DEGLENS	60° Optic Lens	
Bracket	ACCXHB38ADJBRKT	±45° Adjustable Bracket	
Reflector	HBACCXACRYLCCVR	PC Reflector	

DIMENSIONS

