

iGAZER33HDB

Battery Powered Photo Eye



FEATURES

- Adjustable optics:
+/- 90° horizontally
+/- 15° vertically.
- Infrared
- IP55 Protection
- Double rubber seal
- Up to 49 feet range
- Send/receive
- 6V, 4 AAA transmitter battery
- Anti-vandal for industrial use



SPECIFICATIONS

Power supply	12/24 VAC/DC
Operating Temperature	5° to 140° F
TX battery type	6V, 4AAA
RC consumption	47 mA at 12 VAC; 35 mA (inactive) 22 mA at 12 VDC; 16 mA (inactive) 48 mA at 24 VAC; 36 mA (inactive) 24 mA at 24 VDC; 18 mA (inactive)
Wave length	950 nm
Modulation	1.33 KHz
Current commutable by the relay	1 A at 24 V
Range	26 Feet (Low) 49 Feet (High)
Battery Life (low power)	24 months
Battery Life (high power)	14 months



2480 South 3850 West, Suite B
Salt Lake City, UT 84120
(866) 975-0101 • (866) 975-0404 fax
www.transmittersolutions.com

All items are trademarks of their respective holders.

To have your fax number removed from future specials, please call Removal Services - 800-915-2571 ext. 47540 or fax to 866-975-0404.