

HIVE Mini Outdoor Receiver

Stand Alone - 2 or 4 Relay Receiver



FEATURES

- Long Range Receiver up to 1200 feet
- Push to Learn up to 85 remotes
- Exterior Grade Quality/Interior Housing Available
- Momentary, or Latching Relay Options
- Whip Antenna Included
- Coax Antenna Optional
- Available in Low Consumption for Solar Applications



SPECIFICATIONS

Receiver type Superheterodyne Carrier frequency 433,92 MHz Local oscillator frequency 6.6128 MHz Demodulation AM/ASK Local Oscillator VCO / PLL Channel width > 25 KHz Intermediate frequency 10.7 MHz Input sensitivity -115 dBm Local oscillator spurious emissions < -57 dBm

Input load: 50 Ohm

Power supply: 12 / 24 Vac/dc

Consumption:

Steady / 12 Vdc (2 relays excited) 15 mA / 49 mA Steady / 24 Vdc (2 relays excited) 19 mA / 55 mA

Max applicable power 24VA Relay number 2 or 4 Contacts NO, NO/NC Memory capacity 85 user codesTX

security code Rolling code 64 Max code combination number 2 Operating temperature -4°/+158°F

Housing protection IP65

Weight 4.5 oz Overall dimensions 3-1/8 x 3-1/8 x 2 inches





PIERCE BUILDING: 3788 WEST 2270 SOUTH, SUITE E SALT LAKE CITY, UT 84120

(866) 975-0101 • (866) 975-0404 FAX WWW.TRANSMITTERSOLUTIONS.COM