

# STAR1000 COMMERCIAL ACCESS CONTROL RECEIVER

High-Capacity Gate and Commercial  
Door Operator Access Control.



## KEY FEATURES

### HIGH CAPACITY

Holds up to 1,000 remote controls

### NEVER LOSE YOUR DATA

Removable backup memory module

### DELETE SINGLE REMOTE CONTROL

Easy to add, block and delete individual remotes

## SMART

1,000 REMOTE CONTROL CAPACITY.

EASY TO PROGRAM USING THE LCD PROGRAMMING DISPLAY.

QUICKLY BLOCK LEARN PASSPORT LITE REMOTE CONTROLS (10 OR 100) A BOX AT A TIME.

TEMPORARILY SUSPEND USERS WITHOUT DELETING THEIR REMOTE CONTROL FROM MEMORY.

DELETE A SINGLE REMOTE CONTROL WITH ABILITY TO RE-USE THE MEMORY SLOT.

FUNCTIONS AS A STAND-ALONE CONTROLLER.

## RELIABLE

DESIGNED FOR OUTDOOR ENVIRONMENTS RATED IP44 HOUSING.

BACKUP MEMORY MODULE – NEVER LOSE YOUR PROGRAMMED REMOTE CONTROL DATA AND EASILY UPDATE A NEW RADIO USING THE REMOVABLE BACKUP MEMORY MODULE. ALSO IDEAL FOR COPYING INTO A SECOND RECEIVER FOR ANOTHER ACCESS POINT.

## SECURE

SECURITY+ 2.0® RECEIVER COMPATIBLE WITH ALL LIFTMASTER® SECURITY+2.0 REMOTE CONTROLS AND OPERATES ON NARROWBAND, TRI-BAND (310, 315 AND 390 MHz) FREQUENCIES TO VIRTUALLY ELIMINATE RF INTERFERENCE THAT CAN AFFECT PERFORMANCE.

## TOTAL SOLUTION ACCESSORIES:

### 3-BUTTON PASSPORT MAX REMOTE CONTROLS\*\*

Visor, keychain and keychain w/proximity sensor 3-button remotes with unique credentialed IDs. Available individual or 100 pack.



PPV3M / PPK3M / PPK3PHM

### 1-BUTTON PASSPORT LITE REMOTE CONTROLS\*\*

Cost-effective, credentialed 1-button access solutions for gate access only. Visor, keychain and keychain w/proximity sensor. Available in 10 or 100 pack.



PLU1-10 / PPK1-10 / PPK1PH-10 / PLU1-100 / PPK1-100 / PPK1PH-100

### LEARNING REMOTE CONTROLS

2- and 4-button remote controls compatible with Security+ 2.0 technology.



892LT / 894LT

### AC TRANSFORMER

24VAC transformer.



95LM

### REMOTE ANTENNA EXTENSION WITH MOUNTING KIT

Additional 15' and 25' coaxial cables to mount antenna away from metal for optimal range.



86LM / 86LMT

\* Special order available for 100 packs that require specific facility code and start IDs.  
 † Passport Lite Remote Controls with Security+ 2.0 (Tri-Band 310/315/390 MHz) are specifically designed for gate access control and are not compatible with LiftMaster Garage Door Openers.  
 ‡ Passport MAX Remote Controls are compatible with LiftMaster Security+ 2.0 (Tri-Band 310/315/390 MHz) and Security+® (315 MHz or 390 MHz) Residential Garage Door Openers and Commercial Door Operators.

PRODUCT GUIDE  
STAR1000  
COMMERCIAL ACCESS RECEIVER

LiftMaster®

## MASTERFUL ENGINEERING.

### CAPACITIES



-1,000 Device Capacity

### POWER



- 9-30VAC, 9-42VDC Supply Voltage
- 50mA Maximum Operating Current
- 30mA Maximum Standby Current
- 6.0kV Minimum Surge Suppression

### MECHANICS



-IP44 Rated Housing

### DIMENSIONS



-4" W x 6" H x 1.875" D



## STANDARD SPECS.

### WARRANTY

- 1-Year Limited

### RADIO

- Security+ 2.0® Only  
(Tri-Band 310/315/390 MHz) Frequency

### OUTPUTS

- One Form C Relay Output. N/O and COM  
- 1 Amp @ 24VAC/DC Relay Contact Rating

**OPERATING TEMPERATURE** **-40°F to 149°F**  
**(-40°C to 65°C)**

### OPERATING HUMIDITY

- 50% Rh

## SHIPPING.

**SHIPPING WEIGHT** (in lbs.)



### CARTON (1)

- 4.5" W x 9.75" H x 2.0" D
- Receiver
- Antenna
- Mounting Bracket with Two Screws
- Instruction Sheet

### STORAGE/SHIP TEMPERATURE RANGE

-40°F to 185°F @ 50% Rh  
-40°C to 85°C @ 50% Rh

For Support Tools and Training Videos, Visit  
[LiftMasterTraining.com](http://LiftMasterTraining.com)

For More Information, Visit  
[LiftMaster.com/AccessControl](http://LiftMaster.com/AccessControl)

Sales Support: **800.282.6225**  
Technical Support Center: **800.528.2806**  
[LiftMasterDealer.CustHelp.com/App/Ask](http://LiftMasterDealer.CustHelp.com/App/Ask)