

Quantity	Name	Description	Footprint
Resistors			
2	10R/BEAD	Ferrite Bead or 1/4W Metal Film Resistor 1%	L_AXIAL-0.4
8	220R	1/8 or 1/4W Metal Film Resistor 1%	R_AXIAL-0.3
4	620R	1/8 or 1/4W Metal Film Resistor 1%	R_AXIAL-0.3
4	1k	1/8 or 1/4W Metal Film Resistor 1%	R_AXIAL-0.3
2	1k5	1/8 or 1/4W Metal Film Resistor 1%	R_AXIAL-0.3
6	4k7	1/8 or 1/4W Metal Film Resistor 1%	R_AXIAL-0.3
2	6k8	1/8 or 1/4W Metal Film Resistor 1%	R_AXIAL-0.3
20	10k	1/8 or 1/4W Metal Film Resistor 1%	R_AXIAL-0.3
2	20k	1/8 or 1/4W Metal Film Resistor 1%	R_AXIAL-0.3
4	33k	1/8 or 1/4W Metal Film Resistor 1%	R_AXIAL-0.3
4	47k	1/8 or 1/4W Metal Film Resistor 1%	R_AXIAL-0.3
23	100k	1/8 or 1/4W Metal Film Resistor 1%	R_AXIAL-0.3
4	330k	1/8 or 1/4W Metal Film Resistor 1%	R_AXIAL-0.3
2	470k	1/8 or 1/4W Metal Film Resistor 1%	R_AXIAL-0.3
1	3M3	1/8 or 1/4W Metal Film Resistor 1%	R_AXIAL-0.3
Capacitors			
2	1n ceramic	Ceramic Disc Capacitor (Footprint also allows 0805 SMD)	RAD-0.1
4	1n Boxed	Boxed Film Capacitor, Pin spacing 5.08mm	RAD-0.2-B
2	4n7	Ceramic Disc Capacitor (Footprint also allows 0805 SMD)	RAD-0.1
14	100n	Ceramic Disc Capacitor (Footprint also allows 0805 SMD)	RAD-0.1
2	1u	1uf Electrolytic Capacitor, min. 16V / Max Height: 9mm	CAP-D5.0xF2.0
2	10u	10uf Electrolytic Capacitor, min. 16V	CAP-D5.0xF2.0
Transistors / Diodes			
6	2N3906	General Purpose Transistor PNP	TO-92-3_L4.9-W3.7-P1.27-L
2	1N4148	high-speed switching diode	DO-35
2	1N4007	1N4001....1N4007 or 1N5817/18/19	DO-41
4	LED-TH-3mm_G	Green LED 3mm round	LED-TH_BD3.0_GREEN
Controls			
4	B100K Pot	CUTOFF_LP-HP-1,LP-HP-2,RESO	9MM VERTICAL POT
4	B100K Tall Trimmer	CV1A,CV2A,RCV1A,RCV2A,	9MM TALL TRIMMER
9	PJ-301M	CV1,CV2,IN1,IN2,OUT1,OUT2,RCV1,RCV2,V/O1	PJ-301M
2	3296W Trimmer 1k (102)	V/O Trim1,V/O Trim2	RES-ADJ-TH_3296W
1	3296W Trimmer 100k (104)	Offset 2	RES-ADJ-TH_3296W
ICs			
4	IC-Socket 14pin	IC Socket 14pin	PDIP14
3	IC-Socket 16pin	IC Socket 16pin	PDIP16
4	TL074 / TL084	Quad Op-Amp	PDIP14
3	LM13700	Dual transconductance amplifier	PDIP16
Pin Headers / Screws			
3	HDR-M-2.54_1x8	8-Pin Header Male, 2.54mm spacing	HDR-M-2.54_1X8
3	HDR-F-2.54_1x8	8-Pin Socket Female, 2.54mm spacing	HDR-F-2.54_1x8
1	EURORACK10	HDR-M-2.54_2X5 Boxed	EURORACK10
1	M3 Spacer 11mm	M3 spacer 11mm height	
2	M3 Screw Philips Head	M3 screw, max length 6mm	
PCBs			
2	CS-20_10HP_PCB	Main-PCB, Control-PCB	EURO_10HP_PCB
1	CS-20_10HP_PANEL	Front Panel	EURO_10HP_PANEL
1	Power Cable 16-10 pin	Euro rack Power cable 16-10 pin	