

Product Specifications

Item		NB-R1570-EW
Power Supply		120V ~ , 60Hz
Max. Power Consumption		1060W
Length of Power Cord		3.94ft (1.2m)
Water Supply Connection		Direct connection to the water supply
Water Supply Pressure		14.223psi ~ 106.675psi (98 - 735 kPa)
Cleansing	Water Flow Rate	Cleansing 0.55 ℓ/min
		Bidet 0.55 ℓ/min
	Water Pressure Adjustment	5 Levels
	Temp. Adjustment	Normal Temp. 93.2°F (34°C), 98.6°F (37°C), 104°F (40°C)
	Heater Capacity	1000W
	Safety Device	Thermal Fuse, Thermostat, Water Level Sensor
Warm Seat	Temp. Adjustment	Normal Temp. 95°F (35°C), 100.4°F (38°C), 104°F (40°C)
	Heater Capacity	55W
	Safety Device	Thermal Fuse
Dry	Temp. Adjustment	Normal Temp. 122°F (50°C) (5 Levels)
	Heater Capacity	195W
	Safety Device	Thermal Fuse, Bi-metal
Water Supply Temp.		37.4°F (3°C) ~ 95°F (35°C)
Temp. of circumstance for use		37.4°F (3°C) ~ 104°F (40°C)
Product size		410mm X 535mm X 150mm
Product weight		4.8kg

* This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.