

Product Specifications

Item		CASCADE 3000	
Power Supply		120V~ , 60Hz	
Max. Power Consumption		1460W	
Length of Power Cord		3.94ft (1.2m)	
Water Supply Connection		Direct connection to the water supply	
Water Supply Pressure		14.223psi~106.675psi	
Cleansing	Water Flow Rate	Rear	Max. 0.185gal/min
		Front	Max. 0.185gal/min
	Water Pressure Adj.		3 Levels
	Temp. Adjustment		Normal Temp. 93.2F(34C), 98.6F(37C), 104F(40C)
	Heater Capacity		1400W
	Safety Device		Thermal Fuse, Thermostat
Warm Seat	Temp. Adjustment		Normal Temp. 95F(35C), 100.4F(38C), 104F(40C)
	Heater Capacity		55W
	Safety Device		Thermostat
Dry	Temp. Adjustment		Normal Temp. ~ 122F(50C) (5 Levels)
	Heater Capacity		195W
	Safety Device		Thermal Fuse, Bi-metal
Deodorization		Catalytic Deodorization	
Water Supply Temp.		37.4F(3C) ~ 95F(35C)	
Temp. of circumstance for use		37.4F(3C) ~ 104F(40C)	
Product Size	Elongated	1.26ft(W) x 1.74ft(L) x 0.51ft(H) (385mm x 530mm x 155mm)	
	Round Front	1.26ft(W) x 1.62ft(L) x 0.51ft(H) (385mm x 495mm x 155mm)	
Product Weight	Elongated	8.60lbs(4.2kg)	
	Round Front	8.38lbs(4.1kg)	